

1 110066

7-15-87

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-151-21,844 - 00-00

SW SW NW, SEC. 8, T 29 S, R 13 W/E

2970 feet from S section line

4950 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4782

Lease Name Barbee Well # 1-8

Operator: Ensign Operating Company

County Pratt 156.85

Name & Address 621 17th Street, Suite 1800

Well Total Depth 4826 feet

Denver, CO 80293

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8 feet 419

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor H-30, Inc. License Number 5107

Address 251 North Market, Suite 1110, Wichita, KS 67202

Company to plug at: Hour: 9 p.m. Day: 14 Month: 7 Year: 19 87

Plugging proposal received from Rick Davis

(company name) H-30, Inc. (phone) 316-263-2043

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1960' GL  
Anhydrite 780'

1st plug at top of Arbuckle with 25 sx cement, 2nd plug at Anhydrite with 50 sx cement,

3rd plug at <sup>30' below</sup> base of surface pipe with 50 sx cement, 4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement.

Plugging Proposal Received by James R. Kapp  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 4 a.m. Day: 15 Month: 7 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 4730' with 25 sx cement,

2nd plug at 780' with 50 sx cement,

3rd plug at 449' with 50 sx cement,

4th plug at 40' with 10 sx cement,

5th plug to circulate rathole with 10 sx cement.

RECEIVED  
STATE CORPORATION COMMISSION

07-21-87 JUL 21 1987

CONSERVATION DIVISION  
Wichita, Kansas

Remarks: Used 60/40 Pozmix 4% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
(If check did not) observe this plugging.

Signed James R. Kapp  
(TECHNICIAN)

DATE 7-22-87

INV. NO. 17589

7-15

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

# NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date: 7/9/87  
month day year

API Number 15- 151-21,844

OPERATOR: License # 04782  
Name: Ensign Operating Co.  
Address: 621 17th Street, Suite 1800  
City/State/Zip: Denver, Colorado 80293

SW SW NW Sec. 8 Twp. 29 R. 13  West  
2970 Ft. from South Line of Section  
4950 Ft. from East Line of Section  
(Note: Locate well on Section Plat on reverse side)

Contact Person: L. T. Hartnett  
Phone: (303) 293-9999

Nearest lease or unit boundary line: 330 feet  
County: Pratt

CONTRACTOR: License # 5107  
Name: H-30, Inc.  
City/State: Wichita, Kansas 67202

Lease Name: Barbee well # 1-A  
Ground surface elevation: 1960.75 feet MSL  
Domestic well within 930 feet:  yes  no

Well Drilled For:  Oil  Storage  Infield  Mud Rotary  
 Gas  Inj  Pool Ext.  Air Rotary  
 OWWO  Expl  Wildcat  Cable

Municipal well within one mile:  yes  no  
Depth to bottom of fresh water: 200-240  
Depth to bottom of usable water: 300-260

If OWWO: old well info as follows:  
Operator: \_\_\_\_\_  
Well Name: \_\_\_\_\_  
Comp Date: \_\_\_\_\_ Old Total Depth: \_\_\_\_\_

Surface pipe by Alternate:  1  
Surface pipe planned to be set: 400  
Conductor pipe required: 0  
Projected Total Depth: 4750 feet  
Formation: Arbuckle

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.  
Date: 6/30/87 Signature of Operator or Agent: [Signature] Title: Manager, Operations

For KCC Use:  
Conductor Pipe Required: \_\_\_\_\_ feet; Minimum Surface Pipe Required: 280 feet per Alt. DX  
This Authorization Expires: 1-6-88 Approved By: [Signature] 7-6-87

Spud 7:45 AM  
Sat 4:15 PM called 6/40 Res 303-293-9999

Plug Arbuckle SW SW NW Sec. 8 Twp. 29 R. 13  West

## PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep	<u>4750</u>	or formation with	<u>100</u>	feet of	Class A
2nd plug @ ft. deep	<u>900</u>	or formation with	<u>100</u>	feet of	Class A
3rd plug @ ft. deep	<u>450</u>	or formation with	<u>100</u>	feet of	Class A
4th plug @ ft. deep	<u>40</u>	or formation with	<u>40</u>	feet of	Class A
5th plug @ ft. deep		or formation with		feet of	
(2) Rathole to surface minus 5 feet	<u>10</u>	SXS			(b) Mousehole to surface minus 5 feet <u>10</u> SXS

PUSHER Rich Davis

TD 4826 FORMATION Arbuckle

SURFACE PIPE 8 5/8 @ 419

ANHYDRITE 180 ELEVATION 1960.75

STARTING TIME & DATE 7-14-87 9:00 PM

COMPLETION TIME & DATE 7-16-87 4:00 AM

1st PLUG @ 4730 FT. W/ 25 SX

2nd PLUG @ 780 FT. W/ 60 SX

3rd PLUG @ 447 FT. W/ 60 SX

4th PLUG @ 40 FT. W/ 10 SX

RAT HOLE CIRCULATED W/ 10 SX

MOUSE HOLE CIRCULATED W/ 8 SX

WATER WELL PLUGGED W/ 15 SX

CEMENT COMPANY alled

TECHNICIAN Dick

6/40 w/ 479 gell

RECEIVED  
STATE CORPORATION COMMISSION  
JUL 21 1987  
CONSERVATION DIVISION  
Wichita, Kansas