9-30-87 ¹ n5n939 API NUMBER 15- 097-21,183-6000 To:-STATE CORPORATION COMMISSION 120' N C CONSERVATION DIVISION - PLUGGING SECTION W/2 NW SE, SEC. 13 , T 28 S, R 19 W/k 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 2100 feet from S section line 2310 TECHNICIAN'S PLUGGING REPORT feet from E section line Lease Name Hindershot Operator License # 5992 \_\_\_Well  $m{I}$   $^{
m A-1}$ County\_Kiowa Patton Oil Company Operator: 158.76 Name& .. 4885 672 West 4th Well Total Depth Address feet Hoisington, KS 67544 Conductor Pipe: Size \_\_\_\_\_feet\_\_ Surface Casing: Size 8 5/8 feet 517Abandoned Oll Well X Gas Well Input Well SWD Well D&A Other well as hereinafter indicated Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050 Address P.O. Box 347, Chase, KS 67524 Company to plug at: Hour: 9 a.m. Day: 30 Month: Plugging proposal received from <u>Bill Fulls</u> (company name) Kelso Casing Pulling, Inc. were: 45" at 4867' PBTD 4320' Perfs at 4270-78" 1st plug sand back to 4220' and dump 4 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 15 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8" wiper plug and pump 150 sx cement. \_Plugging Proposal Received by \_\_\_\_ Dan Goodrow (TECHNICIAN) Plugging Operations attended by Agent?: All \_\_ X Part Operations Completed: Hour: 1 p.m. Day: 30 Month: ACTUAL PLUGGING REPORT 1st plug sanded back to 4220' and dumped 4 sx cement on top of sand through dump bailer. 2nd plug pumped 3 sx hulls, 15 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, released

8 5/8" wiper plug and pumped 150 sx cement. STATE CORPORATION COMMISSION Maximum pressure 600 psi and shut in 300 psi.

Recovered 2900' of 4½" casing. Remarks: Used 60/40 Pozmix 6% gel by Allied. (If additional description is necessary, use BACK of this form.)
CONSERVATION DIVISION

N Will xxxxxx observe this plugging.

Wichita, Kansas

18420

Signed Richard W. Lachy (TECHNICIAN)