

To: 1 031413  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15- 057-20,545-0000  
E/2 W/2 NE, SEC. 16, T 29 S, R 22 W/E

TECHNICIAN'S PLUGGING REPORT

10-6

1320 feet from N & section line  
1650 feet from E section line

Operator License # 4767  
Operator: Ritchie Exploration, Inc.  
Name & Address: 125 N. Market, Ste. 1000  
Wichita, KS 67202

Lease Name Darst Well # I  
County Ford 35.00  
Well Total Depth 785 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 521

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SNO Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Duke Drilling Co. License Number 5929

Address 310 W. Central, Wichita, KS 67202

Company to plug at: Hour: 10:30 p.m. Day: 5 Month: 10 Year: 19 96

Plugging proposal received from Harvey Moore

(company name) Duke Drilling Co. (phone) 316-267-1331

Work: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 785' with 100 sx cement, 2nd plug at 485' with 40 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement,

5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Durrant (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 2:45 a.m. Day: 6 Month: 10 Year: 19 96

ACTUAL PLUGGING REPORT 1st plug at 785' with 100 sx cement,

2nd plug at 485' with 40 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 35 sx cement,

5th plug to circulate mousehole with 10 sx cement.

Lost circulation at 595'.

Remarks: Used Class A cement 3% cc by Allied.

(If additional description is necessary, use BACK of this form.)

(I, \_\_\_\_\_, do not) observe this plugging.

Signed Steve Durrant (TECHNICIAN)

DATE \_\_\_\_\_

INV. NO. 46716

RECEIVED  
KANSAS (CORP) COM  
1996 OCT - 9 PM 12:19

10-9-1996

FOR KCI USE:

FORM C-1 7/91

EFFECTIVE DATE: 9-21-96

State of Kansas

057-20,545-0000

FORM MUST BE TYPED

DISTRICT #

NOTICE OF INTENTION TO DRILL

FORM MUST BE SIGNED

ALL BLANKS MUST BE FILLED

Must be approved by the K.C.C. five (5) days prior to commencing well

Expected Spud Date 9 25 96 month day year

Spot E/2 W/2 NE Sec 16 Twp 29 S Rg 22W East West

OPERATOR: License # 4767 Ritchie Exploration, Inc. Address: 125 N. Market, Suite 1000 Wichita, KS 67202 Contact Person: Lisa Thimmesch Phone: (316) 267-4375

1320 feet from South North line of Section 1650 feet from East West line of Section IS SECTION X REGULAR IRREGULAR

(NOTE: Locate well on the Section Plat on Reverse Side)

County: Ford

Lease Name: Darst Well #: 1

Field Name: unknown

Is this a Promoted/Spaced Field? yes X no

Target Formation(s): Mississippian

Nearest lease or unit boundary: 890

Ground Surface Elevation: 2438 est feet MSL

Water well within one-quarter mile: yes X no

Public water supply well within one mile: yes X no

Depth to bottom of fresh water: 250

Depth to bottom of usable water: 150 480

Surface Pipe by Alternate: 1 2

Length of Surface Pipe Planned to be set: 500

Length of Conductor pipe required: none

Projected Total Depth: 5450

Formation at Total Depth: Mississippian

Water Source for Drilling Operations:

X well farm pond other

DNR Permit #: APPLY FOR FROM DNR

Will Cores Be Taken? yes X no

If yes, proposed zone:

CONTRACTOR: License #: 5929 Duke Drilling Co.

Well Drilled For: Well Class: Type Equipment:

X Oil Enh Rec Infield X Mud Rotary Gas Storage Pool Ext Air Rotary CWBO Disposal Wildcat Cable Seismic: # of Holes Other

If CWBO: old well information as follows:

Operator: Well Name: Comp. Date: Old Total Depth

Directional, Deviated or Horizontal wellbore? yes X no

If yes, true vertical depth:

Bottom Hole Location:

Exp. 3/16/97

AFFIDAVIT

500' Alt. I Req.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well...

SKID RIG

Pusher: Arvey Moore SPUD DATE: 10-3-96 INIT. SD LENGTH SURFACE PLANNED: 500 FT

RESERVE PIT STATUS- REMOVE FLUID LINED after salt sect. bbls. when done bbls. RATHOLED AHEAD? Y N SIZE HOLE SURFACE PIPE 8 5/8 @ 5 2 1 CONDUCTOR ANHYDRITE T- B- ELEVATION

TD 785 FORMATION RAN PIPE @ DV TOOL ALT II DONE SX Y N

Arbuckle Plug @ Ft. W/ SX Plug @ Council @ Ft. W/ SX Anhydrite Base @ Ft. W/ SX

1 1/2 Base Anyh. @ 785 Ft. W/ 100 SX 740 700 @ 485' Ft. W/ 40 SX 1/2, 1/2 Plug @ Ft. W/ SX

Bottom Surface @ Ft. W/ SX 40' Plug @ 40-0 Ft. W/ 10 SX RAT HOLE CIRC/W SX MOUSE HOLE W/ SX

WATER WELL 35-3X SX (Irr. Well) Pond Hauling TECHNICIAN SD DATE 10-5-96

TYPE OF CEMENT @ class A 2 1/2 inch 30% cc STARTING TIME 10:30 (AM/PM) DATE 10/5 COMPLETION TIME 2:48 (AM/PM) DATE 10/6 CEMENT COMPANY: Allied East Circle 895