1100016

To:	API NUMBER 15-05/ -20,3/4-0000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING	NW <u>NE SE</u> , Sec. <u>36</u> , T <u>29</u> S, R <u>25</u> W/K
WICHITA, KANSAS 67202	feet from N/S section line
TECHNICIAN'S PLUGGING REPORT	feet from W/E section line
Operator License # 5123	Lease Name Amy Unit Well # 4
Operator: Pickrell Drilling Company	CountyFord
Name & 110 North Market, Suite 205 Address Wichita, KS 67202	Well Total Depth 5450 feet 177.13
	Conductor Pipe: Sizefeet
	Surface Casing: Size 8 5/8 feet 564
Abandoned Oil Well Gas Well In	out Well SWD Well D&A_X
Other well as hereinafter indicated	-
Plugging Contractor Pickrell Drilling Compa	any License Number 5123
Address 110 North Market, Suite 205, Wich	nita, KS 67202
Company to plug at: Hour: 6:00 pm Day:	28 Month: <u>April</u> Year:19 84
VERBAL PLUGGING ORDERS GIVEN TO	lerb French
(company name) Pickrell Drilling	
were: to fill hole with heavy mud and s	spot cement through drill pipe
1st plug at 1320' with 50 sx cement	
2nd plug at 840' with 60 sx cement	
solid bridge 3rd plug hulls - plug at 40' cement to s	
5th plug to circulate rathole with 15 sx ce	ement
	Signed Slyde Wiley
	(TECHNICIAN)
Plugging Operations attended by Agent?: All	PartNoneX
Operations Completed: Hour: 10:30 pm Day	28 Month: <u>April</u> Year:19 84
ACTUAL PLUGGING REPORT 1st plug at 1320 wi	th 50 sx cement, 2nd plug at 840' with
60 sx cement, 3rd plug and 4th plug - solid	bridge - hulls - plug at 40° cement to
surface with 10 sx cement, 5th plug to circ	ulate rathole with 15 sx cement
	N
·	, , , , , , , , , , , , , , , , , , ,
	STATE CORPORATION
Remarks: Use 60/40 Pozmix 2% gel 3% cc by	Allied # 322579 STATE CORPORATION COMMISSION MAY 0 7 100
	CONSER. 1984
	CONSERVATION DIVISION Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated and that I (\mbox{disk} / \mbox{did} not) observe this plugging.

INVOICED

OATE 5-8-84

INV. NO. 1427