To:	$\frac{1}{10000000000000000000000000000000000$	API- NUMBER 15- 097-20,840-0000		
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202		C NW NE , SEC.	25 T 27	s, R 16 W/E
		4620	feet from S	section line
TECHNICIAN	N'S PLUGGING REPORT		feet from E	
Operator L	.icense # 5414	Lease Name Clark		
	Trisum/J. Mark Richardson	County Kiowa		- n
Name& Address	155 N. Market, Suite 840	Well Total Depth		
	Wichita, KS 67202	Conductor Pipe:		
•		Surface Casing:	8 5/8	400
Abandoned	Oll Wail X Gas Wall 1			
	Oll Weil X Gas Weil 1 as hereinafter indicated	"PO! #0!!	SAD Mell	D&A
				
	Greensburg Well Service		License Number_	
	03 E. Kansas, Greensburg, KS 67054			
	plug at: Hour: 9 a.m. Day: 1		Year	91
	roposal received from Carl Schield			
(company n	ame) Greensburg Well Service		(phone)	316-723-2204
vere: 41211	at 4669' w/200 sx cement, PBTD 4669'			
lst plug s	and back to 4340° and dump 4 sx cemen	t on top of sand t	hrough bailer,	
2nd plug p	ump 3 sx hulls, 10 sx gel, 50 sx ceme	nt, 10 sx gel, l s	x hulls, releas	e 8 5/8"
wiper plug	and pump 150 sx cement.			
			····	
	Plugging Proposa	l Received by	Case Morris	·
	*		(TECHNICI	AN)
Plugging O	perations attended by Agent?: Ail_	X Part	None_	·
Operations	Completed: Hour: 10 a.m. Day:	19 Month:	Year	:19
ACTUAL PLU	GG:NG REPORT lst plug sanded back to	4340' and dumped	4 sx cement on	top of .
sand bridge	e through bailer,			
2nd plug p	umped down 8 5/8" surface pipe with 3	00 lbs. hulls, 10	sx gel, 50 sx c	ement,
10 sx gel,	100 lbs. hulls, released 8 5/8" wipe	r plug and pumped	150 sx cement:	PRATICAL COMMENTS OF
	essure 900 psi and shut in 300 psi.			
		 :		C307991 2 = 32 91
Romarks: No	sed 60/40 Pozmiy 6% gel by Halliburto	n Recovered 2496		2-30-91
Remarks: Used 60/40 Pozmix 6% gel by Halliburton. Recovered 2496' of 4½" casing				
' (a'ia' \ a'j	kxxxxx) observe this plugging.	2.1	, (). M
DATE	1-10-92	Signed A	len C. T-	Leile 2 8
INV. NO. 343/				
	12-19		,	FORM CP-2/3/