та: у 1 041214	API NUMBER 15-097-20,016-0001
STATE CORPORATION COMMISSION Wichita State Office Bldg PLUGGING SECTION	C NE SW , SEC. 22 , T 27 S, R 16 W/X
130 S. Market, Room 2078	- 1980 feet from S section line
Wichita, KS 67202 /0-17	3300 feet from E section line
Operator License / 5414	Lease Hame Clark A Well 5 3
Operator: J. Mark Richardson	County Kiowa 159.99
Names Address 155 N. Market, #840	Well Total Depth 4923 feet
Wichita, KS 67202	Conductor Pipe: Sizefeet
· · · · · · · · · · · · · · · · · · ·	Surface Casing: Size 8 5/8 feet 368
15-1-and CII Vall Y Gas Vall	Input Well SWD Well D&A
Other well as hereinafter indicated	Tapar sari Dan
<del>-</del>	License Number 31201
•	•
Address 303 E. Kansas, Greensburg, KS 67054	
Plugging proposal received from Carl Schio	
(company name) Greensburg Well Service (phone) 316-723-2204  were: 4½" at 4922 w/275 sx cement, CIBP 4645, Perfs at 4561-4888 (7 sets), BP @ 4700	
1st plug sand back to 4500° and dump 4 sx co	ement on top of sand through bailer,
	02 4/
3rd plug at 390' with 50 sx cement,	10-23-96 5 5
4th plug at 40' with 10 sx cement.	Steve Pfeifer
Plugging Proposal Received by Steve Pieter (TECHNICIAN)	
Plugging Operations attended by Agent?: All X Part None	
Operations Completed: Hour: 7 p.m. Day: 17 Honth: 10 Year: 19 96	
ACTUAL PLUGGING REPORT 1st plug sanded back to 4500' and dumped 4 sx cement on top of	
sand bridge through bailer,	
Loaded hole with gel and spotted plugs through 4½" casing:	
2nd plug at 1100' with 50 sx cement,	
3rd plug at 390° with 50 sx cement,	<u> </u>
4th plug at 40° with 10 sx cement.	· · · · · · · · · · · · · · · · · · ·
Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2310' of 4½" casing.	
(Afradaltional description is necessary, use BACK of this form.)	
observe this plugging.  • DATE 10-28-96	Held Held
1/6/23 -	SIgned SIGNETANT TUTEL
INV. 10-17	FORM CP-2/3