

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
266 N. Main St., Ste. 220
Wichita, KS 67202-1513

API Well Number: 15-099-20493-00-00
Spot: NENENW Sec/Twnshp/Rge: 21-34S-20E
5103 feet from S Section Line, 2930 feet from E Section Line
Lease Name: LINK Well #: 1
County: LABETTE Total Vertical Depth: 423 feet

Operator License No.: 9386
Op Name: GUS JONES CABLE TOOL SERVICE, LL
Address: 149 RD 25
ELK CITY, KS 67344

String	Size	Depth (ft)	Pulled (ft)	Comment
PROD	5.5	423		

Well Type: ST UIC Docket No: _____ Date/Time to Plug: _____
Plug Co. License No.: 9386 Plug Co. Name: GUS JONES CABLE TOOL SERVICE, LLC
Proposal Rcvd. from: DONALD (GUS) JONES Company: GUS JONES CABLE TOOL SERVIC Phone: (620) 332-7637

Proposed Plugging Method: DRILLED WITH 9 INCH BIT TO 265 FT. CORED WITH 4 INCH CORE BIT TO 365 FT. REAMED WITH 9 INCH BIT TO 423 FT. SET 5 1/2 INCH CASING TO 423 FT CEMENTED WITH HIGH TEMPERATURE LUMINITE CEMENT WITH 40 PER CENT SILICA FLOUR. 1 1/2 INCH TUBING WELDED TO OUTSIDE OF CASING FOR THERMOCOUPLE. PERFORATED FROM 355 TO 367 FT WITH 2 SHOTS PER FOOT. ACID FRACTURED AT 1100 PSI. PERFORATIONS WERE SQUEEZED WITH 35 SACKS CEMENT. DRILLED OUT, PERFORATED 361-367 WITH 4 SHOTS PER FOOT. PERFORATIONS WOULDN'T TAKE FLUID. HYDROJET PERFORATED AT 362 AND 366 FT. ACIDIZED WITH 450 GALLONS 7 1/2 % HCl.

Plugging Proposal Received By: RUSSELL HINE WitnessType: COMPLETE (100%)
Date/Time Plugging Completed: 05/19/2009 9:00 AM KCC Agent: RUSSELL HINE

Actual Plugging Report:

Ran 3/4" in thermocouple plugged with 4 sacks of portland. Hooked to 5-1/2" and created rate of flow and then pumped 50 sacks of 60/40 pozmix w/ 5% gel. Shut in at 500psi.

Perfs:

RECEIVED
KCC DIST # 3
JUL 15 2015
CHANUTE, KS

RH

Remarks: ~~CORRECTED FOOTAGES/GPS 7/15/2015~~

Plugged through: CSG

CKM

District: 03

Signed Russell Hine
(TECHNICIAN)

KCC WICHITA

JUL 21 2015

RECEIVED