

1110122

2-8

API NUMBER 15-097-21,267-0000

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

NE NE NW, SEC. 4, T 28 S, R 20 (W) E
4950 feet from S section line
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 4243

Lease Name Henry Well # 4-1

Operator: Cross Bar Petroleum, Inc.

County Kiowa 177.13

Name & Address P.O. Box 20080

Well Total Depth 5450 feet

Wichita, KS 67208

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 450

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Eagle Drilling, Inc. License Number 5380

Address 2759 South Broadway, Wichita, KS 67216

Company to plug at: Hour: 10:30 p.m. Day: 7 Month: 2 Year: 19 89

Plugging proposal received from Butch Steinert

(company name) Eagle Drilling, Inc. (phone) 316-945-9935

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 860-70
1st plug at 1200' with 50 sx cement, 2nd plug at 480' with 40 sx cement,
3rd plug at 40' with 10 sx cement, 4th plug to circulate rathole with 15 sx cement,
5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by James R. Kapp (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 12 a.m. Day: 8 Month: 2 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug at 1200' with 50 sx cement,
2nd plug at 480' with 40 sx cement,
3rd plug at 40' with 10 sx cement,
4th plug to circulate rathole with 15 sx cement,
5th plug to circulate mousehole with 10 sx cement.

RECEIVED STATE CORPORATION COMMISSION

FEB 15 1989 2-15-1989 CONSERVATION DIVISION Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. (If additional description is necessary, use BACK of this form.)

INVOICED (XXXX) did not observe this plugging.

Signed James R. Kapp (TECHNICIAN)

DATE 2-17-89

INV. NO. 23957 2-8

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date... February 1 1989

API Number 15-097-21,267-0060

OPERATOR: License # 4243
Name Cross Bar Petroleum, Inc.
Address P.O. Box 20080
City/State/Zip Wichita, Kansas 67208
Contact Person Albert Brensing
Phone 316/683-5956

NE NE NW Sec. 4 Twp. 28 S. Rg. 20
4950 Ft. from South Line of Section
2970 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5380
Name Eagle Drilling, Inc.
City/State Wichita, Kansas

Nearest lease or unit boundary line 330 feet
County Kiowa
Lease Name Henry Well # 4-1
Ground surface elevation 2310 feet MSL
Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no
Depth to bottom of fresh water 100 feet
Depth to bottom of usable water 288 feet 310
Surface pipe by Alternate: 1X 2
Surface pipe planned to be set 450 feet
Conductor pipe required None
Projected Total Depth 5500 feet
Formation Arbuckle

Well Drilled For: Well Class: Type Equipment:
X Oil Storage Infield X Mud Rotary
X Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 1-11-89 Signature of Operator or Agent Albert Brensing Title President

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 330 feet per Alt.
This Authorization Expires 7-11-89 Approved By AKM 1-11-89

EFFECTIVE DATE: 1-16-89

Move in 1-30-89 set 450' of 8 1/8"

NE NE NW Sec. 4 Twp. 28 S. Rg. 20

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. Anhydrite or formation with 50 Sacks feet of. 60-40. Poz. 6% gel.
2nd plug @ ft. deep. 440' 1300' or formation with 50 Sacks feet of.
3rd plug @ ft. deep. Base of Surface or formation with 40 Sacks feet of.
4th plug @ ft. deep. 40' or formation with 10 Sacks feet of.
5th plug @ ft. deep. Rathole or formation with 15 Sacks feet of.
(2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet

PUSHER Ratched Stewart
TD 5450 FORMATION
SURFACE PIPE 450' @ 8 1/8" 950
ANHYDRITE 860-70 ELEVATION
STARTING TIME & DATE 10:30 PM
COMPLETION TIME & DATE Mid 2-8-89
1st PLUG @ 1200 FT. W/ 50 SX
2nd PLUG @ 480 FT. W/ 40 SX
3rd PLUG @ 40 FT. W/ 10 SX
4th PLUG @ FT. W/ SX
RAT HOLE CIRCULATED W/ 15 SX
MOUSE HOLE CIRCULATED W/ 10 SX
WATER WELL PLUGGED W/
CEMENT COMPANY Halcrow
TECHNICIAN

RECEIVED
PROPOSITION COMMISSION
15 1989
CONSERVATION DIVISION
Wichita, Kansas