

7-15-1937

State Approved

STATE OF KANSAS
STATE CORPORATION COMMISSION

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission,
800 Bittling Building,
Wichita, Kansas

JUL 15 1937

WELL PLUGGING RECORD
OR
FORMATION PLUGGING RECORD

15-173-01734-0000

Strike out upper line
when reporting plug-
ging of formations.

Sedgwick County, Sec. 1 Twp. 26 Rge. (E) 1 (W)

Location as "NE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ " or footage from lines SE-NE-NE-NE

Lease Owner Phillips Petroleum Company

Lease Name A. E. Difford Well No. 2

Office Address Bartlesville Oklahoma

Character of Well (Completed as Oil, Gas or Dry Hole) Oil Well

Date, well completed March, 25 1929

Application for plugging filed June, 19, 1937 193

Application for plugging approved June, 19, 1937 193

Plugging Commenced 6-22 1937

Plugging Completed 6-24 1937

Reason for abandonment of well or producing formation Exhausted oil well

If a producing well is abandoned, date of last production 4-9-35 193

Was permission obtained from the Conservation Division or its agents before plugging was com-
menced? Yes

Mr. H. C. Smith

Name of Conservation Agent who supervised plugging of this well

Producing formation Viola Lime Depth to top 3382 Bottom 3392 Total Depth of Well 3396 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
Sand	6 BW	1115	1120	20"	57'	None
Sand	8 BW	1325	1335	15 $\frac{1}{2}$ "	445	445
Lime	1 BW	1505	1510	13 $\frac{3}{8}$	1365	1365
Lime	2 BW	1710	1715	10 $\frac{3}{4}$	2427	2427
Lime	HFV	2380	2385	8 $\frac{1}{4}$	3035	2910
Lime	2 BW	2615	2620	7	3380	3360
Lime	3 BW	2640	2645			
Sandy Lime	HFV		3050			

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Dumped in 10 sacks of regular Portland cement on top of cave and tools lost in hole. On top of cement placed 500' of mud. Bridged hole at 200' and put 15 sacks of regular Portland cement on top of bridge. Mudded hole to top and capped hole with 5 sacks of cement.

PLUGGING
FILE SEC-1-T-26R1W
BOOK PAGE-95 LINE-2

(If additional description is necessary use BACK of this sheet)

Correspondence regarding this well should be addressed to _____

Address _____

STATE OF Kansas, COUNTY OF Sedgwick, ss.

C. E. Klein (employee of owner) or (owner or operator) of the above-described well,

being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) C. E. Klein

(Address)

SUBSCRIBED AND SWORN to before me this 19 day of July, 1937.

My commission expires April 24 1940.

M. A. Miles

Notary Public.

Formation record A. E. Difford #2,

Soil	10		Lime	1795	
Sand HFW	45		Shale	1820	
Shale	95	20" Casg. 56'	Lime	1825	
Red rock	100		Shale	1840	
Shale	155		Lime	2035	
Lime	160		Lime & shale	2060	
Shale	185		Shale	2080	
Lime	200		Shale	2135	
Shale	205		Shale	2210	
Lime	225		Shale	2230	
Shale	245		Lime	2235	
Lime	255		Shale	2245	
Shale	260		Lime	2275	
Lime	265		Shale	2305	
Shale	275		Lime	2330	
Lime	280		Sand HFW	2400	
Shale	290		Lime	2460	10" Casg. 2407
Lime	335		Lime shells	2495	
Shale	330		Shale	2525	
Shale	410		Shale	2540	
Red rock	415		Lime	2575	
Shale	450		Shale	2585	
Lime	500	15" Casg. 452'	Lime	2620	Show oil 2600
Lime shells	545		Shale	2630	
Lime	615		Lime 3 BW	2705	
Shale	620		Shale	2710	
Lime shells	690		Shale	2715	
Lime	715		Lime	2725	
Shale	725		Shale	2780	
Red rock	730		Lime shells	2795	
Lime	810		Shale	2815	
Shale	815		Lime	2825	
Lime	845		Shale	2845	
Shale	870		Lime	2860	
Red rock	875		Shale (cave)	2880	
Lime	915		Shale	2890	
Shale	980		Lime	2905	
Shale	1010		Lime shells	2935	
Shale & shells	1065		Lime	2940	
Shale 6 BW	1115		Shale	2945	
Sand	1120		Lime	2970	
Shale	1125		Shale (cave 3005)	3030	8" casg. 3010
Shale	1130		Chat	3045	
Lime	1135		Sandy lime HFW	3060	
Shale	1155		Lime (cave 3080)	3290	
Lime	1160		Shale	3322	
Shale	1190		Lime 3325	3325	
Lime	1200		Shale	3350	7" casg. 3350
Shale	1225		Shale	3382	
Red rock	1230		Sandy lime	3392	
Shale	1265		Shale	3396	
Lime	1270		Total Depth	3396	
Shale	1300				
Shale	1325				
Sand 8 BW	1335				
Shale	1355	12 1/2" Casg. 1352			
Lime	1360				
Shale	1365				
Lime	1375				
Shale	1500				
Lime	1505				
Shale	1305				
Shale	1410				
Lime	1450				
Shale & shells	1455				
Shale	1475				
Lime	1480				
Shale & shells	1505				
Lime 1 BW	1515				
Shale	1535				
Shale	1555				
Lime & shale	1595				
Shale & shells	1685				
Lime 2 BW	1715				
Shale	1730				
Lime	1735				
Shale	1760				