TANSAS

Form CP-3 Rev. 6-4-68

## STATE CORPORATION COMMISSION

## CONSERVATION DIVISION AGENT'S REPORT

J. Lewis Brock
Administrator P. O. Box 17027 Wichita, Kansas 67217  RECEIVED STATE CORPORATION COMMISSION
Wichita, Kansas 67217 GOPY MAY 3 - 1974
CONSERVATION DIVISION
Wichita, Kansas
Complete Address 209 E William Wichita, KS
Lease Name Dunn Well No. 2
Location C SE/SW Sec.25 Twp. 278Rge 19 (E) W
County Klowa Total Depth 4825
Abandoned Oil Well X Gas Well Input Well SWD Well D & A
Other well as hereafter indicated
Plugging Contractor Pipe Pullers Inc
Address Box 486 Ellinwood, KS License No. 462
Operation Completed: Hour 2:00 PM Day 15 Month 4 Year 1974
The above well was plugged as follows:
The above well was plugged as follows:  328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 42 long string
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 42 long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100 sacks cement to surface.
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100 sacks cement to surface.
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100 sacks cement to surface.
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100 sacks cement to surface.  Pumped by Halliburton Cementing Co Great Bend, KS
328 ft 8 5/8 surface cemented with 300 sacks. 4808 ft 4½ long string cemented with 150 sacks. Open hole. Sand to 4790 ft, 4 sacks cement with bailer. Pulled 2231 ft 4½. Pump 2 sacks hulls, 10 gel, 100 sacks cement to surface.