

TYPE

AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

Compt. _____

SIDE ONE

(Rules 82-3-130 and 82-3-107)

This form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ninety (90) days after the completion of a well, regardless of how the well was completed.

FOR INFORMATION REGARDING THE NUMBER OF COPIES TO BE FILED AND APPLICATIONS REQUIRING COPIES OF ACO-1 FORMS SEE PAGE TWO (2), SIDE TWO (2) OF THIS FORM.

F _____ Letter requesting confidentiality attached.

C Yes Attach ONE COPY of EACH wireline log run (i.e. electrical log, sonic log, gamma ray neutron log etc.)***Check here if NO logs were run _____.

PLEASE FILL IN ALL INFORMATION. IF NOT AVAILABLE, INDICATE. IF INFORMATION LATER BECOMES AVAILABLE, SUBMIT BY LETTER.

LICENSE # 6417 EXPIRATION DATE June 30, 1984

OPERATOR CHAMPLIN PETROLEUM COMPANY API NO. 15-057-20,323

ADDRESS 6441 N.W. Grand, Suite 300 COUNTY Ford

Oklahoma City, OK 73116 FIELD Minneola

** CONTACT PERSON Marilyn Day PROD. FORMATION _____

PHONE (405) 840-5521

PURCHASER N/A LEASE McCune "C"

ADDRESS _____ WELL NO. 1

WELL LOCATION SW

DRILLING CONTRACTOR Damac Drilling, Inc. 1900Ft. from South Line and

ADDRESS P. O. Box 1164 2310Ft. from West Line of

Great Bend, KS 77279 the SW (Qtr.) SEC25 TWP29S RGE 25 (W)

PLUGGING CONTRACTOR Sargent Casing Pulling WELL PLAT _____ (Office Use Only)

ADDRESS P. O. Box 506 KCC _____

Liberal, KS 67901 KGS _____

TOTAL DEPTH 5500' PBTD 5240' SWD/REP _____

SPUD DATE 5-17-83 DATE COMPLETED 6-18-83 PLG.

ELEV: GR 2589' DF 2595' KB 2598' NGPA _____

DRILLED WITH (CABLE) ROTARY (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE N/A

Amount of surface pipe set and cemented 1274' DV Tool Used? Yes

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion _____. Other completion _____. NGPA filing _____.

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.


A F F I D A V I T

MARILYN DAY, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. The statements and allegations contained therein are true and correct.

Marilyn Day
(Name)

SUBSCRIBED AND SWORN TO BEFORE ME this 1st day of July,



[Signature]
(NOTARY PUBLIC)
STATE CORPORATION COMMISSION

MY COMMISSION EXPIRES: 10-8-83

JUL 05 1983

** The person who can be reached by phone regarding any questions concerning this information.

CONSERVATION DIVISION
Wichita, Kansas

SIDE TWO

ACO-1 WELL HISTORY

OPERATOR CHAMPLIN PETROLEUM COMPANY LEASE McCune "C" SEC. 25 TWP. 29SRGE. 25 (W)

FILL IN WELL INFORMATION AS REQUIRED:

WELL NO. 1

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.		SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.		
FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
<input checked="" type="checkbox"/> Check if no Drill Stem Tests Run.				
<input checked="" type="checkbox"/> Check if samples sent to Geological Survey				
Water, Sand & Red Bed	0	417	Nuclear Log	3500-5422'
Red Bed & Shale	417	710	DIL	1230-5494'
Red Bed	710	1275	DN-CD	3500-5492'
Red Bed & Shale	1275	2090		
Lime & Shale	2090	5500		
RTD		5500		

If additional space is needed use Page 2,

Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Conductor		16"		58'	Grout	6 yds	
Surface	12-1/4"	8-5/8"	24#	1274'	Litewate	500	2% CaCl, 1/4# Flocele/sk
					Class H	200	3% CaCl
Production	7-7/8"	5-1/2"	14#	5499'	50-50 Pozmix	150	18% salt .75% CFR-2, 12 1/2# Gilsonite/sk

LINER RECORD			PERFORATION RECORD		
Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
			4		5269-5273'
TUBING RECORD					
Size	Setting depth	Packer set at			
		CIBP @ 5240'			

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD

Amount and kind of material used	Depth interval treated
1000 gal. MRS-1 acid w/24 ball sealers	5269-5273'
Frac w/11,500 gal. foam diesel oil, 6500# 20-40 sd, 231,000 ft ³ nitrogen	5269-5273'

Date of first production	Producing method (flowing, pumping, gas lift, etc.)	Gravity
---	---	---
Estimated Production -I.P.	Oil 0 bbls.	Gas 0 MCF
	Water % 0 bbls.	Gas-oil ratio --- CFPP
Disposition of gas (vented, used on lease or sold)		Perforations Morrow 5269-5273'