

STATE CORPORATION COMMISSION
Wichita State Office Bldg. - PLUGGING SECTION SE SE NE NW, SEC. 19, T 27 S, R 33
130 S. Market, Room 2078
Wichita, KS 67202

TECHNICIAN'S PLUGGING REPORT
3980 feet from S section line
2740 feet from E section line

Operator License # 5447 Lease Name Frey C Well # 2

Operator: OXY USA Inc. County Haskell 87.91

Name & Address P.O. Box 300 Well Total Depth 2705 feet
Tulsa, OK 74102

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 809

Abandoned Oil Well _____ Gas Well Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated _____

Plugging Contractor Halliburton Services License Number _____

Address _____

Company to plug at: Hour: 10:30 a.m. Day: 23 Month: 9 Year: 19 97

Plugging proposal received from Reid Wilson

(company name) Halliburton Services (phone) 316-629-3578

was: 4 1/2" at 2702' w/600 sx cement, PBTD 2680', Perfs at 2618-30, 2654-58, 2682-95'

1st plug pump 300 lbs. hulls and 200 sx Howco lite cement down 4 1/2" casing.

Check backside.

Plugging Proposal Received by Scott Alberg (TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 11:30 a.m. Day: 23 Month: 9 Year: 19 97

ACTUAL PLUGGING REPORT 1st plug pumped down 4 1/2" casing with 2 sx hulls and 175 sx cement.

Maximum pressure 500 psi and shut in 350 psi.

2nd plug pumped 5 sx cement down backside. Shut in pressure 50 psi.

Remarks: Used 65/35 Pozmix 6% gel 3% cc by Halliburton. No casing recovery.

(If additional description is necessary, use BACK of this form.)

Observe this plugging.

DATE SEP 26 1997 Signature (TECHNICIAN)

INV. NO. 49155 9-23

RECEIVED
KANSAS CORP COM
SEP 26 12:12

9-25-97

AS