1030080

To:	API NUMBER 15- 037- 20304 CCC)
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION	SE _, Sec. 17 , T 27 S, R 24 W/K
200 COLORADO DERBY BUILDING	
WICHITA, KANSAS 67202	2310 feet from X/S section line
TECHNICIAN'S PLUGGING REPORT	feet from W/E section line
Operator License #	Lease Name Barnes Well # 1-H
Operator: Pickwill Drilling Company Name & 110 North Market, Suite 205 Address Wichita, KS 67202	Well Total Depth 5200 feet 169.00
•	Conductor Pipe: Sizefeet
,	Surface Casing: Size 8 5/8 feet 514
Abandoned Oil Well Gas Well Inp	ut Well SWD Well D&A X
Other well as hereinafter indicated	
Plugging Contractor Company tools	-
Address Same	,
Company to plug at: Hour: 10 pm Day: 1	7th Month: January Year:1984
VERBAL PLUGGING ORDERS GIVEN TO Herb French	
(company name) Pickrill Drilling Company	(phone) 262-8427
were: to fill hole with heavy mud and spo	t cement through drill pipe.
lst plug at 1320' with 50 sx cement	;
2nd plug at 540' with 50 sx "	
Solid bridge 3rd plug hulls - plug at 40' -> ce	ment to surface with 10 sx cement
	10 sx cement. plug water well with 5 sx
cement.	Signed Steve a Comment
	(TECHNICIAN)
Plugging Operations attended by Agent?: All_	PartNoneX
Operations Completed: Hour: 9:00 am Day:	18 Month: January Year:19 84
ACTUAL PLUGGING REPORT 1st plug at 1320' wi	th 50 sx cement, 2nd plug at 540' with
50 sx cement, third and 4th plugs -	solid bridge - hulls - plug at 40'
	ment. Plug water well with 5 sx cement.
Comment to surrate with to sa com	ione, Tang water well with 5 SA Coment.
Remarks: Use 60/40 Pozmix, 2% gel, 3% cc	
by Allied Cement	,
·	

I hereby certify that the above plugging instructions were given as herein stated and that I (did / did not) observe this plugging.

INVOICED

RECEIVED STATE CORPORATION COMMISSION

JAN 23 1984

CONSERVATION DIVISION Wichita, Kansas Gigned Steve Alexant

FORM CP-2/3 Rev. 9-82