SIDE ONE TIDAVIT OF COMPLET	ION FORM (REV) ACO-1
This form shall be filed in duplicate with the Kansas Corporation Commission, 200 Coin- rado Derby Building, Wichita, Kansas 67202, within ten days after the completion of the well, regardless of how the well was completed. Attach separate letter of request if the information is to be held confidential. If	
confidential, only file one copy. Information on side one will be of public record and side two will then be held confidential.	
Circle one: 0il, Gas, Dry, SWD, OWWO, Injection. Type and complete ALL sections. Applications must be filed for dual completion, commingling, SWD and injection, T.A. Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). KCC # (316) 263-3238. (Rules 82-2-105 & 82-2-125)	
OPERATOR TXO PRODUCTION CORP.	API NO. 15-097-20,738-0000
ADDRESS 200 W. Douglas, Ste. 300	COUNTY Kiowa
Wichita, KS 67202	FIELD Greensburg East
**CONTACT PERSON Harold R. Trapp	PROD. FORMATION_Kinderhook
PHONE 265-9441	- LEASE Thompson
PURCHASER Unknown	WELL NO. #1 "H"
ADDRESS N/A	WELL LOCATION C SE SE
	660' Ft. from South Line and
DRILLING H=30, Rig. #5 CONTRACTOR	660' Ft. from East Line of
ADDRESS 251 N. Water	the 21 SEC-275 TWP.17W RGE.
Wichita, KS 67202	WELL PLAT
PLUGGING N/A CONTRACTOR	KCC
ADDRESS	KGS
······································	Use)
TOTAL DEPTH 4800 PBTD 4785	
SPUD DATE 3-15-81 DATE COMPLETED 5-28-82	
ELEV: GR 2135 DF N/A KB 2143	*
DRILLED WITH (CANEXXX) (ROTARY) XXXXX TOOLS	
Amount of surface pipe set and cemented NA DV Tool Used? N/A A F F I D A V I I	
STATE OF KANSAS , COUNTY OF	Sedgwick SS, I,
Harold R. Trapp OF LAWFUL AGE, BEING FIRST DULY SWORN UPON HIS OATH,	
DEPOSES THAT HE IS <u>District Geologist</u> (FOR)(XXXX) <u>TXO Production Corp.</u>	
OPERATOR OF THE Thompson LEAS	SE, AND IS DULY AUTHORIZED TO MAKE
THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERAT	FOR, THAT WELL NO. "H" #1 ON
SAID LEASE HAS BEEN COMPLETED AS OF THE 28th DAY OF May , 19 82 , AND THAT	
ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID WELL IS TRUE AND CORRECT.	
FURTHER AFFIANT SAITH NOT. BONNIE J. HOLCON COTATY PUBLIC STATE OF KARTAN FLACOLETE 1/23/	(55 (5) Darold R Tron
SUBSCRIBE CORRESCON DAY O	OF June , 1982.
APR 0 7 1983	Bonsie (Holnond
MY COMMIGONESRIVATION DIVISION 223 85 Wichita, Kansas	NOTARY PUBLIC
**The person who can be reached by phone regarding any questions concerning this infor-	
mation. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.	

DEPTH

HAME

Show ell important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

FORMATION DESCRIPTION, CONTENTS, ETC.

LOG TOPS Herington 2358 -215 -344 Towanda 2487 Cottonwood 2860 -717 Foraker 3010 -867 -1029Wabaunsee 3172 3370 -1227Tarkio 3518 -1375Howard Topeka 3612 -1469Heebner, 3948 -1805 -18453988 Douglas Iatan 4102 -19594121 -1978 Lansing -2215 Dennis 4358 4410 -2267 Swope 4453 -2310 Hertha B/Kansas City 4486 -2343 Cherokee 4614 -2471-2509 Miss. 4652 Kinderhook 4686 -2543 4746 -2603 Viola RTD 4800 LTD 4801 DST_#1, 3012-40' (Foraker), w/results as follows: IFP/30": 69-178#, good blow ISIP/60": 1208# FFP/30": 178-248#, good blow FSIP/60": 1028# Rec: 30' DM, 430' SW 4688-4700' (Kinderhook), w/results as follows: IFP/30": 43-43#, good incr. to strong blow ISIP/60": 1504# FFP/60": 4354#, GTS in 1", 50 MCFD incrl to 81 MdFD FSIP/120": 1547# Rec: 120' DM Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used) Size casing set Weight Ibs/ft. Setting depth Type and parcent odditives Type cement Sacks 400 Surface 121 8-5/8" 24# 402' RECEIVED 4-1/2" 4799' Production 10.5# 175 STATE CORPORATION COMMISSION APR 0 7 1983 CONSERVATION DIVISION Wichita, Kansas LINER RECORD PERFORATION RECORD Top, ft. Sacks coment Bottom, ft. Shots per ft. Sixe & type Death Interval 2 JSPF (22 h.) 4707-09' & 4694-4704' ÑΙΑ N/A N/A Kinderhook TUBING RECORD Sixe Setting depth Pucker set at 2-3/8" 4688 ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD Amount and kind of meterial used Depth Interval treated Dumped 250 gals acetic acid + 40 bbls 2% KCl wtr Acidized w/500 gals 10% MCA + 500 gals 12% HCl w/3% HF 4707-09' & 4694-4704' Fraced w/285 sxs 16-30# sand w/complex gel Date of Hrst production Producing method (flewing, pumping, ges lift, etc.) Gravity N/A <u>5-28-82</u> flowing % 24 BW Ses-oil ratio RATE OF PRODUCTION PER 24 HOURS MCF N/A 180 MCFD CFPS Disposition of gas (vented, used on lease or said) Perforations 4707-09' & 4694-4704' Sold Panhandle Fastern

KANSAS DRILLERS LOG

Texas Oil &mGas Corporation

•cc. 21 ,275 m.17W

660' FSL

raam Thompson "H" No.]

county Kiowa

ROTARY TOTAL DEPTH 48001
COMM. April 15, 1981
COMP. April 23, 1981
COMPRACTOR H-30, INC.
ISBUED 4-10/81

. 21251 6 1

10.0/4"

10 3/4"

8 5/8" Set at 402' cemented with 400 sxs cement
5 1/2"
4 1/2" Set at 4799' cemented with 200 sxs cement

ELEVATION 2135' G.L.

dieted with 200 bas cemente

FIGURES INDICATE BOTTOM OF FORMATIONS

Sand and Red Bed 433' 2,028' Red Bed Red Bed and Shale 2,121' 2,560' Shale and Lime 2,815' Lime and Shale 3,030' Shale and Lime Lime and Shale 3,560' 4,026' Shale and Lime 4,315' Lime and Shale Shale and Lime 4,410' 4,575' Lime and Shale Shale and Lime 4,655! Lime and Shale 4,700' 4,705 Shale and Lime 4,8001 Lime and Shale 4,800' Rotary Total Depth

I hereby certify the above and foregoing to be a true and correct log of the above described well as shown by the drilling reports.

H-30, INC.

Gary Younger

State of Kansas) ss:
County of Sedgwick)

Subscribed and Sworn to before me, a Notary Public, in and

Minister said county and state this 10th day of April, 1981.

Elsie Willison - Notary Public

My Commission Expires:

July 25, 1982

 $\langle \zeta \rangle$

RECLIVED STATE CORPORATION COMMISSION

APR 0 7 1983

CONSERVATION DIVISION Wichita, Kansas