

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
266 N. Main St., Ste. 220
Wichita, KS 67202-1513

API Well Number: 15-077-21825-01-00
Spot: S2NENWNW Sec/Twnshp/Rge: 11-32S-7W
360 feet from N Section Line, 990 feet from W Section Line
Lease Name: PARSONS TRUST 3207 Well #: 11-2H
County: HARPER Total Vertical Depth: 4417 feet

Operator License No.: 35053
Op Name: TAPSTONE ENERGY, LLC
Address: PO BOX 1608
OKLAHOMA CITY, OK 73101

| String | Size | Depth (ft) | Pulled (ft) | Comments |
|--------|-------|------------|-------------|--------------|
| COND | 18 | 60 | | 36 sx cement |
| L1 | 4.5 | 9607 | | 435 SX |
| PROD | 7 | 4620 | 1150 | 185 SX |
| PROD | 7 | 4624 | | 185 SX |
| SURF | 9.625 | 691 | | 340 SX |
| SURF | 9.625 | 696 | | 340 SX |

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 07/31/2015 12:00 AM
Plug Co. License No.: 8733 Plug Co. Name: DUNKIN, JERRY, INC.
Proposal Rcvd. from: DONNIE Company: JERRY DUNKIN, INC. Phone: _____

Proposed Plugging Method: AS KCC RULES & REGS

Plugging Proposal Received By: STEVE VANGIESON WitnessType: PARTIAL
Date/Time Plugging Completed: 07/31/2015 12:00 AM KCC Agent: STEVE VANGIESON

Actual Plugging Report:

CIBP @ 3500' & 4 SXS CEMENT. RECOVERED CASING FROM 1150' & LAYED OUT. RAN 2 3/8" TUBING TO 1150' AND SPOTTED 50 SXS CEMENT. PULLED TUBING TO 740' AND SPOTTED 75 SXS CEMENT. PULLED TUBING TO 200' & CIRCUALTED CEMENT TO SURFACE.

Perfs:

| Top | Bot | Thru | Comments |
|------|------|------|----------|
| 4620 | 9563 | | CSG |


Remarks: JERRY DUNKIN - COMMON CEMENT. - MD = 9569

Plugged through: TBG

District: 02

Received
KANSAS CORPORATION COMMISSION
AUG 20 2015
CONSERVATION DIVISION
WICHITA, KS

Signed



(TECHNICIAN)

9/3/15 ckm