

To: 1 030852
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 3536

Operator: Ramco Drilling Services, Inc.
Name & Address: P.O. Box 99
Belpre, OH 45714

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 8:30 a.m. Day: 20 Month: 9 Year: 19 87

Plugging proposal received from Ross Crawford

(company name) Red Tiger Drilling Company (phone) 316-263-1201

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2277' Anhydrite 1412-50'

- 1st plug at 1450' with 50 sx cement,
- 2nd plug at 611' with 50 sx cement,
- 3rd plug at 40' with 10 sx cement,
- 4th plug to circulate rathole with 10 sx cement.

Plugging Proposal Received by Steve Durrant (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 10 a.m. Day: 20 Month: 9 Year: 19 87

ACTUAL PLUGGING REPORT 1st plug at 1450' with 50 sx cement,

- 2nd plug at 611' with 50 sx cement,
- 3rd plug at 40' with 10 sx cement,
- 4th plug to circulate rathole with 10 sx cement.

RECEIVED
SEP 23 1987
9-23-87

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.
(if additional description is necessary, use BACK of this form.)

INVOICED
(operator did not) observe this plugging.

DATE 9-24-87

Signed Steve Durrant (TECHNICIAN)

INV. NO. 18248

09-20 OCT 29 1987

9-20-87

API NUMBER 15-097-21,250-0000

SE NW, SEC. 23, T. 27 S, R. 20 W/E

3300 feet from S section line

3300 feet from E section line

Lease Name Russell Fralick Well # 1

County Kiowa 160.06

Well Total Depth 4925 feet

Conductor Pipe: Size _____ feet

Surface Casing: Size 8 5/8 feet 571

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date. 09 15 87
month day year

API Number 15-097-21,250

OPERATOR: License # 5336
Name RAMCO Drilling Services, Inc.
Address P.O. Box 99
City/State/Zip Belpre, OH 45714
Contact Person Bob Williamson or David Gocke
Phone (614) 423-9591

SE NW Sec. 23 Twp. 27 S. Rg. 20 East
3300 West
3300 Ft. from South Line of Section
Ft. from East Line of Section

CONTRACTOR: License # 5302
Name Red Tiger Drilling Company
City/State Wichita, Kansas

(Note: Locate well on Section Plat on reverse side)
Nearest lease or unit boundary line 660 feet
County Kiowa

Well Drilled For: Well Class: Type Equipment:
X Oil Storage Infield X Mud Rotary
X Gas Inj X Pool Ext. Air Rotary
— OWWO — Expl — Wildcat — Cable

Lease Name Russell Fralick Well # 1
Ground surface elevation 2277 feet MSL
Domestic well within 330 feet: — yes X no
Municipal well within one mile: — yes X no

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth

Depth to bottom of fresh water 170
Depth to bottom of usable water 300
Surface pipe by Alternate: 1 X 2
Surface pipe planned to be set 550
Conductor pipe required
Projected Total Depth 4900 feet
Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.
Date 09/02/87 Signature of Operator or Agent Title Vice President/Engineering

For KCC Use:
Conductor Pipe Required 320 feet; Minimum Surface Pipe Required 320 feet per Alt. 1 X
This Authorization Expires Effective 9-8-87 Approved By 9-3-87

*More in 9-10-87
5501.25/8"*

SE NW Sec. 23 Twp. 27 S. Rg. 20 East
West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep. Base Anhydrite	or formation with	50 sx	feet of	60/40 Pozmix 6% Gel
2nd plug @ ft. deep. 40' Below Surf.	or formation with	50 sx	feet of	60/40 Pozmix 6% Gel
3rd plug @ ft. deep. 0-40' cs	or formation with	10 sx	feet of	60/40 Pozmix 6% Gel
4th plug @ ft. deep	or formation with		feet of	
5th plug @ ft. deep	or formation with		feet of	

(2) Rathole to surface minus 5 feet (b) Mousehole to surface minus 5 feet

PUSHER	Gloss Crawford	15 sx
TD	4925 FORMATION Miss	
SURFACE PIPE	8 3/8 @ 571	
ANHYDRITE	1450 ELEVATION 2277	
STARTING TIME & DATE	8:30 AM 9-20-87	
COMPLETION TIME & DATE	10 9-20-87	
1st PLUG @	1450 FT. W/ 50 SX	
2nd PLUG @	611 FT. W/ 50 SX	
3rd PLUG @	40 FT. W/ 10 SX	
4th PLUG @	FT. W/ SX	
RAT HOLE CIRCULATED W/	10 SX	
MOUSE HOLE CIRCULATED W/	SX	
WATER WELL PLUGGED W/	SX	
CEMENT COMPANY	Hallebitter	
TECHNICIAN	60/40 Poz 620	10 sx