• F	PI NUMBER <u>15-097-20,653-000</u> <u>C NE</u> SEC. <u>24</u> , T <u>27</u> S, R <u>16</u> W
CONSERVATION DIVISION - PLUGGING SECTION	3960 FEET FROM SOUTH SECTION LINE
WICHITA STATE OFFICE BLDG., 130 S. MARKET _	1320 FEET FROM EAST SECTION LINE
· ·	EASE NAME <u>BUTLER-THOMPSON</u> WELL # <u>1-24</u>
TECHNICIAN'S PLUGGING REPORT 12/8 CC	DUNTY KIOWA 149 76
	ELL TOTAL DEPTH 4608 FEET
OPERATOR: VINCENT OIL CORP. PR	RODUCTION CSG: SIZE 4½" @ 4608' WITH 200 SX
NAME AND 125 N MARKET, SUITE 1075 SU	URFACE CASING: SIZE 85%" @ 371' WITHSX
ADDRESS WICHITA, KS 67202	
ABANDONED OIL WELL X GAS WELL INPUT W	WELLD/A
OTHER WELL AS HEREINAFTER INDICATED	
PLUGGING CONTRACTOR QUALITY WELL SERVICE	LICENSE NUMBER 31925
ADDRESS 249 BETH DRIVE, STERLING, KS 67579)
COMPANY TO PLUG AT: HOUR: 3:30 PM DAY:	08MONTH:12YEAR:1999
PLUGGING PROPOSAL RECEIVED FROM RICHARD MC	CINTYRE
(COMPANY NAME) QUALITY WELL SERVICE	(PHONE) <u>316-727-3410</u>
WERE: PERFS AT 4449-53, 4454-55	
SANDED BACK TO 4400' AND PUT 4 SX CEMENT ON	TOP OF SAND BRIDGE THROUGH BAILER. LOAD HOLE
WITH GEL AND SPOT PLUGS THROUGH 4%" CASING.	1ST PLUG AT 1100' WITH 50 SX CEMENT.
2ND PLUG AT 400' WITH 50 SX CEMENT. 3RD PLU	JG AT 40' WITH 10 SX CEMENT.
·	
1	PLUGGING PROPOSAL RECEIVED BY STEVE PFEIFER
PLUGGING OPERATIONS ATTENDED BY AGENT?: ALI	L X PARTNONE
OPERATIONS COMPLETED: HOUR: 4:30 PM DAY	Y: 08 MONTH: 12 YEAR: 1999
ACTUAL PLUGGING REPORT	······································
SANDED BACK TO 4400' AND PUT 4 SX CEMENT ON	TOP OF SAND BRIDGE THROUGH BAILER. RECEIVED
LOAD HOLE WITH GEL AND SPOT PLUGS THROUGH 43	KI CASING. 1ST PLUG AT KAHOMO CONTOUNTS (SAME EMENT
2ND PLUG AT 400' WITH 50 SX CEMENT. 3RD PLU	JG AT 40' WITH 10 SX CEMENT. DEC 10 1999
I (DID) OBSERVE THES PLUGGING: STATE 22399 ()(a/03/a)	CONSERVATION DIVISION RECOVERED 2410' OF 4%" CASING ACHITA KS IPTION IS NECESSARY, USE BACK OF THIS FORM.) IGNED (TECHNICIAN) FORM CP-2/3
AN NO OUTO TO	