9. Alternate No. 1

| TO BI | FILED | WITH | THE | STATE | CORPO | RATION | COMMISSION | | |
|-------------------------------|-------|------|-----|-------|-------|--------|------------|--|--|
| PRIOR TO COMMENCEMENT OF WELL | | | | | | | | | |

| ı | Operator Cities Service Oil Company | | | | | | | |
|----|---|--|--|--|--|--|--|--|
| | 209 E. William, 710 Sutton Place Bldg. | | | | | | | |
| | Address Wichita, Kansas 67202 | | | | | | | |
| | 1 | | | | | | | |
| | Contractor Sage Drilling Company, Inc. | | | | | | | |
| ٠. | 500 Bitting Building | | | | | | | |
| | Address Wichita, Kansas 67202 | | | | | | | |
| | | | | | | | | |
| 3. | Type of Equipment: Rotary X Cable Tool | | | | | | | |
| l. | Well to be Drilled for: Oil X Gas | | | | | | | |
| | DisposalOther | | | | | | | |
| í. | Depth of Deepest Fresh Water within 1 mile 125 ft. | | | | | | | |
| 3. | Depth of Municipal Water Well within 3 miles None ft. | | | | | | | |
| | Depth to Protect all Fresh Waterft. | | | | | | | |
| | Amount of Surface Casing to be set 1000 ft | | | | | | | |

| (For office use only) | > |
|----------------------------------|---|
| Starting Date June 13, 1973 | |
| CountyPratt | |
| Sec 27 Twp 29 S Rge 13 W | ζ |
| Spot Location 2110 FSL - 330 FEL | |
| Nearest Lease Line330 ft | |
| Lease Name Harre 1 "D" | |
| Well No6 | |
| Est. Total Depth 4635 ft | |


401 North 15-151-20.311

REMARKS: 13-3/8" set @ 100' - cement to surface OPERATOR STATES THAT HE WILL COMPLY WITH K. S. A. 55-128

8-5/8" set @ 1000' - cement to surface

Signature of Operator

C. E. Forrester, Region Petroleum Engineer



State Corporation Commission of Kansas

Conservation Division

P.O. Box 17027

Wichita, Kansas 67217

RECEIVED STATE CORPORATION COMMISSION

JUN 1 2 1973

CONSERVATION DIVISION Wichita, Kansas

(IF PREFERRED, MAIL IN ENVELOPE)