

1060145

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- CORE
SE/4, SEC. 23, T 27 S, R 29 W/E

720 feet from W/S section line
640 feet from E/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5118

Lease Name Einsel G Well # 1-C

Operator: TGT Petroleum Corp.

County Kiowa

Address 209 East William

Well Total Depth 1260 feet

Wichita, KS 67202

Conductor Pipe: Size _____ feet

Surface Casing: Size 5 1/2 feet 201

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A _____

Other well as hereinafter indicated Core

Plugging Contractor TGT Petroleum Corp. License Number 5118

Address 209 East William, Wichita, KS 67202

Company to plug at: Hour: 2:00 pm Day: 1 Month: February Year: 19 84

Plugging proposal received from Bill Stanka

(company name) TGT (phone) 316-262-6489

were: Squeezed through 5 1/2" swedge on 5 1/2" casing with 2 sx gel, 2 sx hulls and 65 sx cement. Cement used was common cement with 2% gel and 3% cc.

Halliburton Co. accomplished the cementing with Maximum pressure at 450# and shut in pressure at 300#.

Plugging Proposal Received by Paul Luthi
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part _____ None _____

Operations Completed: Hour: 3:00 pm Day: 1 Month: February Year: 19 84

ACTUAL PLUGGING REPORT Squeezed through 5 1/2" swedge on 5 1/2" casing with 2 sx gel, 2 sx hulls and 65 sx cement. Cement used was common cement with 2% gel and 3% cc.

Halliburton Co. accomplished the cementing with max. pressure at 450# and shut-in pressure at 300#.

Remarks: Use common cement cement 2% gel, 3% cc. by Halliburton
(if additional description is necessary, use BACK of this form.)

I (did / ~~did not~~) observe this plugging.

Signed Paul A. Luthi
(TECHNICIAN)