

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-185-21873-0000

NENE, Sec. 3, T 25 S, R 14 W/4

660 feet from N/8 section line

660 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5056

Lease Name Dykes Well # 1-3

Operator: F.G. Holl  
Name & Address 6427 East Kellogg  
Wichita, Kansas

County Stafford

Well Total Depth 4390' feet 142.68

Conductor Pipe: Size \_\_\_\_\_ feet \_\_\_\_\_

Surface Casing: Size \_\_\_\_\_ feet \_\_\_\_\_

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sterling Drilling Company License Number 5142

Address P.O. Box 129 Sterling, KS 67579

Company to plug at: Hour: 4:00pm Day: 28 Month: October Year: 19 83

VERBAL PLUGGING ORDERS GIVEN TO Tom Meyers

(company name) Sterling Drilling Company (phone) \_\_\_\_\_

were: To use 60/40 poz mix 2% gel 3% cc

1st plug @ 870' w/50sx 2nd plug @ 330'

w/40sx, 3rd plug @ 40' w/Solid Bridge Plug+10sx

Circulate 10sx in rat hole, Circulate 10sx

in mousehole

Signed Richard W. Lacey  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 8:30pm Day: 28 Month: October Year: 19 83

ACTUAL PLUGGING REPORT Plugged as proposed in above paragraph

Halliburton pumped the cement

Remarks: \_\_\_\_\_

I hereby certify that the above plugging instructions were given as herein stated and that I (did / did not) observe this plugging.

INVOICED RECEIVED  
DATE 11-14-83 STATE CORPORATION COMMISSION  
INV. NO. 6059-W NOV 2 1983

Signed Richard W. Lacey  
(TECHNICIAN)

11-2-83