

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API number: 15-051-20,245-00-00

E2 NE SE /4 SEC. 03, 14 S, 20 W  
1980 feet from S section line  
1650~~30~~ feet from E section line

Operator license# 5252 Lease Dinkel well # 2

Operator: R.P. Nixon Operations, Inc. County Ellis

Address: 207 West 12th Street Well total depth 3854 feet  
Hays, Kansas 67601 Conductor Pipe: 0 inch @ 0 feet  
Paul Nixon Surface pipe 8 5/8 Inch @ 200 feet

Aband. oil well X, Gas well    , Input well    , SWD    , D & A    

Plugging contractor: Allied Cementing - Co Tools License#    

Address: Hays, Kansas - Hays, Kansas 67601

Company to plug at: Hour: P.M. Day: 2 Month: November Year: 93

Plugging proposal received from: Paul & Dan Nixon

Company: R.P. Nixon Operatons, Inc. Phone: 913-628-3834

Were: 8 5/8" 200' cwc. S.P. w/165 sxs. cement. 4 1/2" casing @ 3848'  
w/150 sxs. cement - open hole ar buckle. 8 5/8" x 4 1/2" annulus cement  
visable in braden head. Possible squeeze. No record. Proposal 300 sxs.  
60/40 pozmix - 10% gel - 5 sxs. hulls. Perferate 4 1/2" casing at 795' -  
1550' - 2250'. Spot and displace all cement through tubing - load  
4 1/2" casing bottom to top with cement. Squeeze annulus with cement.  
Shut in under pressure.

Plugging Proposal Received by: Marion Schmidt  
Plugging operations attended by agent? All[X ], Part[     ], None[     ]

Completed: Hour: 6:00P.M., Day: 2, Month: November, Year: 93

Actual plugging report: Nixon ordered 300 sxs. 60/40 pozmix - 10% gel -  
5 sxs. hulls. Spotted and displaced all cement through tubing - annulus  
cement visable in braden head. Perf. 4 1/2" casing @ 795' - 1550' - 2250'  
1) 2 3/8" tubing @ 3100' spotted and displaced 100 sxs. cement with 2 sxs  
hulls mixed in. 2) 2 3/8" tubing @ 1600' spotted 100 sxs. cement with 1  
sx. hulls. 3) 2 3/8" tubing @ 800' spotted 100 sxs. cement with 2 sxs.  
hulls. Order more cement then 4) 2 3/8" tubing @ 480' spotted 120 sxs.  
cement did not circulate. On 11-03-93 ran 2 3/8" tubing to 527' spotted  
25 sxs. cement. Cement circulated out of 4 1/2" casing. Squeezed 4 1/2"  
casing w/5 sxs. cement. Max. pressure 500# P.S.I. Shut In @ 400# P.S.I.

Remarks: By: Allied Cement.  
Condition of casing(in hole): GOOD     BAD X Anhy. plug: YES X NO      
Bottom plug(in place): YES X, CALC    , NO     Dakota plug: YES X, NO      
Plugged through TUBING X, CASING    . Elevation:     GL

I did[X ] / did not[     ] observe the plugging. Marion Schmidt

HO (agent)  
Form CP-2/3