STATE OF KANSAS STATE CORPORATION COMMISSION

WELL PLUGGING RECORD . K. Å.R. −82-3-117

API	NUMBER15-185-21,417-0000

•	202	•			LEASE N	AME Harrison		
		TYPE O	R PRI	NT	WELL NU	MBER #1		
					_ Ft. from S Section Lin			
		office within 30 days.				Ft. from E Section Line		
LEASE OPERATOR Arr	owhead Petro	leum, Inc	<u> </u>		SEC.36	_TWP. <u>25_</u> RGE. <u>13W_(</u> E)or(W		
P.O. Box 1393 ADDRESS Great Bend, KS 67530						COUNTY <u>Stafford</u>		
PHONE#(316) 793-6					Date We	II Completed		
Character of Well _	Oil	•			Pluggin	g Commenced 11/3/88		
(OII, Gas, D&A, SWD	, Input, Water	Supply Wel	(1		Pluggin	g Completed 11/15/88		
The plugging propos	al was approved	1 on				(date		
						C District Agent's Name)		
Producing Formation		Depth	to T	op	Botte	omT.D. <u>4329'</u>		
Show depth and thic	kness of all wa	ater, oil a	nd ga	s formati	ons.			
OIL, GAS OR WATER	RECORDS	<u> </u>		C	ASING RECO	RD		
Formation	Content	From	То	Size	Put In	Pulled out		
			<u> </u>	8 5/8	350	none 2780		
			.	4 1/2	4305	2780		
-		<u> </u>	·	<u> </u>	\			
Describe in detail, placed and the met were used, state to Plugged bott 2780', plugg	hod or methods the character om with sand	used in in of same a to 4080' ith 300#	trodu nd de , ra hull	cing it in pth placen 4 sachs, 10 sa	nto the ho ed, from cs cement acks gel,	Ing where the mud fluid le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz.		
Describe in detail, placed and the met were used, state to Plugged bott 2780', plugg 10 sacks, ge	hod or methods the character om with sand ed surface w	used in in of same a to 4080' ith 300# , release	troduc nd de , ra hull d pl	pth plac n 4 sach s, 10 sa ug 125 s	nto the ho ed, from as cement acks gel, sacks 60/	le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz.		
Describe in detail, placed and the met were used, state to Plugged bott 2780', plugg 10 sacks, ge	hod or methods the character om with sand ed surface w 1 100# hulls tional descript	used in in of same a to 4080' ith 300# , release	troduced of the state of the st	cing it in pth place n 4 sach s, 10 sach ug 125 s	nto the ho ed, from cs cement acks gel, sacks 60/	le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz. form.)		
Describe in detail. placed and the met were used, state i Plugged bott 2780', plugg 10 sacks, ge	hod or methods the character om with sand ed surface w 1 100# hulls tional descript ntractor Kels	used in in of same a to 4080' ith 300# , release	troduc nd de , ra hull ed pl essar	cing it in pth place n 4 sach s, 10 sach ug 125 s	nto the ho ed, from cs cement acks gel, sacks 60/ CK of this	le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz. form.) License No. 6050		
Describe in detail, placed and the met were used, state to Plugged bott 2780', plugg 10 sacks, ge (if additional and the met were used, state to Plugged bott 2780', plugg 10 sacks, ge	hod or methods the character om with sand ed surface w 1 100# hulls tional descript ntractor Kels	used in in of same a to 4080' ith 300# , release ion is nec	troduc nd de , ra hull d pl essar Pull	cing it in pth place n 4 sach s, 10 sach ug 125 s y, use BA ling, In elso Cas	nto the ho ed, from cs cement acks gel, sacks 60/ CK of this	le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz. form.)		
Describe in detail, placed and the met were used, state to Plugged bott 2780', plugg 10 sacks, ge (if additional address P.O. Box	hod or methods the character om with sand ed surface w 1 100# hulls tional descript ntractor Kels K 347 NSIBLE FOR PLUG	used in in of same a to 4080' ith 300# , release ion is nec	troduc nd de , ra hull d pl essar Pull	cing it in pth place n 4 sach s, 10 sach ug 125 s	nto the ho ed, from cs cement acks gel, sacks 60/ CK of this	le. If cement or other p feet to feet each s , shot @3230', 3010' 50 sacks cement, 40 poz. form.) License No. 6050		