

To: 1 090769  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15-185-23,033-0000  
165' S of -  
NW NW SE, SEC. 34, T 25 S, R 11 ~~WXX~~  
2145 feet from S section line  
2310 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
3911  
Operator License / \_\_\_\_\_

Lease Name Zink Well # 2-34  
County Stafford 137.24

Operator: RAMA Operating Co., Inc.  
Name  
Address P.O. Box 159  
Stafford, KS 67578

Well Total Depth 4223 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 10 3/4 feet 268

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A   
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sterling Drilling Company License Number 5142

Address P.O. Box 1006, Pratt, KS 67124-1006

Company to plug at: Hour: 8 p.m. Day: 20 Month: 12 Year: 19 96

Plugging proposal received from Vaughn Thompson

(company name) Sterling Drilling Company (phone) 316-672-9508

Work: to fill hole with heavy mud and spot cement through drill pipe  
1st plug at 600' with 50 sx cement, 2nd plug at 290' with 75 sx cement,  
3rd plug at 40' with 15 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
5th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by Steve Middleton (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 9:30 p.m. Day: 20 Month: 12 Year: 1996

ACTUAL PLUGGING REPORT 1st plug at 600' with 50 sx cement,  
2nd plug at 300' with 75 sx cement,  
3rd plug at 40' with 15 sx cement,  
4th plug to circulate rathole with 15 sx cement,  
5th plug to circulate mousehole with 10 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
I ~~will~~ and not observe this plugging.

DATE JAN 03 1997

INV. NO. 47240

Signature \_\_\_\_\_ (TECHNICIAN)

12-24-96  
RECEIVED  
MAY 24 4 1:09  
MAY 24 4 1:09  
MAY 24 4 1:09

Effective Date: 9-22-96

Must be approved by the K.C.C. five (5) days prior to commencing well.

District # 1  
SGA7  Yes  No  
Expected Spud Date 9/23/96

Spot 165' S OF  
NW - NW - SE Sec 34 Twp 25 S, Rg 11W  
2145 feet from South line of section  
2310 feet from East line of section  
Is section  Regular  Irregular?

Operator: License # 3911  
Name: RAMA Operating Co., Inc.  
Address: P.O. Box 159  
City/State/Zip: Stafford, KS 67578  
Contact Person: Robin L. Austin  
Phone: 316/234-5191

(Note: Locate well on the Section Plat on Reverse Side)  
County: Stafford  
Lease Name: Zink Well #: 2-34  
Field Name: Bauman

Contractor: License # 5142  
Name: Sterling Drilling Company

Is this a Prorated/Spaced Field:  yes  no  
Target Formation (s): Viola

Well Drilled For: Well Class: Type Equipment  
 Oil  ENH Rec  Infield  Mud Rotary  
 Gas  Storage  Pool Ext.  Air Rotary  
 OWWO  Disposal  Wildcat  Cable  
 Seismic;  # of Holes  Other

Nearest lease or unit boundary: 330  
Ground surface elevation: EST. 1820 feet MSL  
Water well within one-quarter mile:  yes  no  
Public water supply well within one mile:  yes  no  
Depth to bottom of fresh water: 98' 180'  
Depth to bottom of usable water: 200'  
Surface pipe by Alternate:  1  2

If OWWO: old well information as follows:  
Operator  
Well Name:  
Comp. Date: Old Total Depth

Length of surface pipe planned to be set: 250  
Length of conductor pipe required: 0  
Projected total depth: 4200  
Formation at total depth: Viola  
Water source for drilling operations:  
 well  farm pond  other

Directional, Deviated or Horizontal wellbore?  Yes  No  
If yes, true vertical depth:  
Bottom Hole Location:

Will cores be taken?:  yes  no  
If yes, proposed zone:

Exp. 3/17/97 Affidavit

220' Alt. I. Reg.

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101, et. seq. it is agreed that the following minimum requirements will be met:

- 1. Notify the appropriated district office prior to spudding of well;
- 2. A copy of the approved notice of intent to drill shall be posted on each drilling rig;

RECEIVED  
KANSAS OCEAN CORP.  
1996 DEC 24 A 1:09

Pusher Thompson INIT 84  
SPUD DATE 12-15-96  
LENGTH SURFACE PLANNED:  
RESERVE PIT STATUS- REMOVE FLUID LINED  
after salt sect. bbls. when done bbls.  
RATHOLED AHEAD? Y N SIZE HOLE  
SURFACE PIPE 34 @ 268 CONDUCTOR  
ANHYDRITE T- B- ELEVATION  
TD 4225 FORMATION  
RAN PIPE @ DV TOOL ALT II DONE  
SX Y N  
Arbuckle Plug @ Ft. W/ SX  
Plug./Council @ Ft. W/ SX  
Anhydrite Base @ 600 Ft. W/ 50 SX  
1/2 Base Anyh. @ Ft. W/ SX  
1/2, 1/2 Plug @ 360 Ft. W/ SX  
Bottom Surface @ 290 Ft. W/ 75 SX  
40' Plug @ 40 Ft. W/ 15 SX  
RAT HOLE CIRC/W 5 SX MOUSE HOLE W/ 10 SX  
WATER WELL SX (Irr. Well Pond Hauling)  
TECHNICIAN SM DATE 609  
TYPE OF CEMENT 69467a  
STARTING TIME 8: (AM/PM) DATE 12-20  
COMPLETION TIME 9:30 (AM/PM) DATE 12-20  
CEMENT COMPANY Allied #1484