To: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING SECTION COO COLORADO DERBY BUILDING WICHITA, KANSAS 67202 TECHNICIAN'S PLUGGING REPORT		APT NUMBER 15- 185-21,245A 000	
		SE NW SE, SEC. 20 , T 25 S, R 13 W/K	
		1650feet from \$ section line	
		1650feet from E section line	
Operator L	Icense #7261	Lease Name Curtis Well # 1	
Name&	Pate Dombaugh Petroleum	County Stafford /37.83	
	804 Union Center Building	Well Total Depth 4241 feet	
-	Wichita, KS 67202		
_		Conductor Pipe: Sizefeet	
_		501 1000 0051 lig: 5120106T	
• •		_ Input Well D&A	
Other well	as hereinafter indicated		
Plugging Co	ontractor Pratt Well Service, 1	Inc. License Number 5893	
	D. Box 847, Pratt, KS 67124		
Company to	plug af: Hour: 2 p.m. Day:	20 Month: 11 Year:19 89	
	roposal received from Ju	 	
_	eme) Pratt Well Service, Inc.	(phone)	
	at 4297' Perfs at 4141-50, 3566		
Ist plug sa	and back to 3500' and dump 5 sx o	cement on top of sand through bailer,	
2nd plug pu	ump 4 sx hulls, 10 sx gel, 50 sx	cement, 10 sx gel, 1 sx hulls, release 8 5/8"	
wiper plug	and pump 125 sx cement.		
	Plugatia Pass		
	Flugging From	osal Received by Richard Lacey (TECHNICIAN)	
Plugging Op	perations attended by Agent?: Al	II <u>X</u> PartNone	
		21 Month: 11 Year: 19 89	
		ack to 3500' and dumped 5 sx cement on top of	
ACTUAL PLUG		ick to 3300 and dumped 3 sx dement on top of	
sand throug	gh bailer,	with 400 lbs. hulls, 10 sx gel, 50 sx cement,	
sand throug	gh bailer, umped into 8 5/8" surface casing	with 400 lbs. hulls, 10 sx gel, 50 sx cement,	
sand throug 2nd plug pu 10 sx gel,	gh bailer, umped into 8 5/8" surface casing	with 400 lbs. hulls, 10 sx gel, 50 sx cement, wiper plug and pumped 125 sx cement (1960) psi.	
sand through 2nd plug pur 10 sx gel, Pumping pre	gh bailer, mped into 8 5/8" surface casing 100 lbs. hulls, released 8 5/8"	with 400 lbs. hulls, 10 sx gel, 50 sx cement, wiper plug and pumped 125 sx cement (150) psi.	
sand through 2nd plug pur 10 sx gel, Pumping pre 5½" casing	gh bailer, imped into 8 5/8" surface casing 100 lbs. hulls, released 8 5/8" essure 0-800 psi and shut in 400 still in hole from 1800 to 2426	with 400 lbs. hulls, 10 sx gel, 50 sx cement, wiper plug and pumped 125 sx cement (150) psi.	

DATE $\frac{12-7-89}{26689}$ INV. NO. $\frac{26689}{26689}$

Igned Duan K

(TECHNICIAN)