## KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| Type Tes  | t:                       |   |  |   | (                                  | (See Instruc                               | tions on Rev  | verse Side   | )                             |   |                                |                |   |  |
|---|--------------------------|---|--|---|------------------------------------|--|---|--|-------------------------------|---|--------------------------------|----------------|---|--|
| ☐ O   | en Flo                   | w   |  |   | Test Date                          | 01   |   |  | ۸D                            | l No. 15  |                                |                |   |  |
| <b>√</b> De                                       | eliverab                 | ilty  |  |   | 10/1/15                            |  |   |  |                               | 007-2   | 00-00                          |                |   |  |
| Company   |                          | PER   | ATING CC   | MPANY, LLC  | ;                                  |  | Lease<br>JAHAY                                      |  |                               | 23,87   | <b>2</b> 5                     | Well Nu        | ımber   |  |
| County<br>BARBE                                   | <br>R                    |   | Locat<br>NW Ni                                     | ion<br>SE SW  | Section<br>31                      |  | TWP<br>33 S   |  | RNG (E                        | (W)   | ,                              | Acres A        | Attributed  |  |
| Field<br>KOCHI <i>E</i>                           | `                        |   |  |   | Reservoi<br>MISSIS                 |  | <del></del>   |  | Gas Ga                        | thering Conn  | ection                         |                |   |  |
| Completi<br>7/3/12                                | on Date                  | е   | _  |   | Plug Bac<br>5049                   | k Total Dep                                | th  |  | Packer S<br>NONE              | Set at  |                                | ·              | •   |  |
| Casing S<br>5.500                                 | ize                      |   | Weigt<br>15.50                                     | 4.950 5074 4612 4700  |                                    |  |   |  |                               |   |                                |                |   |  |
| Tubing S<br>2.875                                 | ize                      |   | Weigt<br>6.500                                     | ght Internal Diameter Set at Perforations To  |                                    | То   |   |  |                               |   |                                |                |   |  |
| Type Cor<br>SINGLE                                |                          | ) (De   | escribe)   |   | Type Flui<br>WATE                  | d Productio                                | n   |  | Pump U<br>PUMF                |   | Plunger? Yes                   | / No           |   |  |
| Producin  | _                        | (Anr  | rulus / Tubin                                      | g)  | % C                                | Carbon Diox                                | ide   |  | % Nitrog                      | gen   | Gas Gr                         | avity - (      | Э,  |  |
| Vertical D  |                          | ')  |  |   |                                    | Pres                                       | sure Taps   |  |                               |   | (Meter F                       | Run) (P        | rover) Size   |  |
|   | Buildu                   | o: :  | Shut in 9/3  | 0/15 2  | 0at                                |  | (AM) (PM)   | Taken_10   | )/1/15                        | 20  | at                             |                | (AM) (PM)   |  |
| Well on L   | .ine:                    | ;   | Started  | 2   | 0 at                               | <del></del>                                | (AM) (PM)   | Taken  |                               | 20  | at                             | (              | (AM) (PM)   |  |
|   |                          |   |  | _   |                                    | OBSERVE                                    | D SURFACE   | DATA   |                               |   | Duration of Shut-              | in             | Hours   |  |
| Static /<br>Dynamic<br>Property                   | Orific<br>Size<br>(inche | 9   | Circle one:<br>Meter<br>Prover Press.<br>psig (Pm) | Pressure Differential in Inches H <sub>2</sub> 0  | Flowing<br>Temperature<br>t        | Well Head<br>Temperature<br>t              | (P, ) or (P,  | Pressure<br>) or (P <sub>a</sub> )                     | Wellhe<br>(P <sub>w</sub> ) ∘ | Tubing<br>ad Pressure<br>r (P <sub>t</sub> ) or (P <sub>c</sub> ) | ·Duration<br>(Hours)           |                | d Produced<br>Barrels)                                      |  |
| Shut-In   |                          |   | paig (Fili)  | inches H <sub>2</sub> 0   |                                    |  | 650   | psia   | 265                           | psia  | 24                             |                |   |  |
| Flow  |                          |   | _  |   |                                    |  |   |  |                               |   |                                |                |   |  |
|   |                          |   |  | <del></del>   | <del></del>                        | FLOW STF                                   | REAM ATTRI  | BUTES  |                               |   |                                |                | r- 1  |  |
| Plate<br>Coeffied<br>(F <sub>b</sub> ) (F<br>Mcfd | ient<br>,)               |   | Circle one:<br>Meter or<br>ver Pressure<br>psia    | Press<br>Extension<br>P <sub>m</sub> x h  | Grav<br>Fac<br>F                   | tor  | Flowing<br>Temperature<br>Factor<br>F <sub>II</sub> | Fa   | iation<br>ctor<br>:<br>pv     | Metered Flow<br>R<br>(Mcfd)                                       | v GOR<br>(Cubic Fer<br>Barrel) | eV             | Flowing<br>Fluid<br>Gravity<br>G <sub>m</sub>               |  |
|   |                          |   |  |   |                                    |  | · · ·   |  |                               | _   |                                |                |   |  |
|   |                          |   |  |   | (OPEN FL                           | OW) (DELIV                                 | ERABILITY)  | CALCUL   | ATIONS                        |   |                                | = 0.2          | <br>07  |  |
| (P <sub>c</sub> ) <sup>2</sup> =                  | <del></del>              | _:_   | (P <sub>w</sub> ) <sup>2</sup> =                   | Choose formula 1 or 2   | P <sub>d</sub> ≡<br>·I             | <del></del>                                |   | <sub>c</sub> - 14.4) +                                 | 14.4 = <u> </u>               | <del>:</del>  | (P <sub>d</sub> ) <sup>2</sup> |                | <del></del>   |  |
| $(P_o)^2 - (P_a)^2$<br>or<br>$(P_c)^2 - (P_d)^2$  |                          | (P <sub>c</sub> ) <sup>2</sup> - (P <sub>w</sub> ) <sup>2</sup> |  | <ol> <li>P<sub>c</sub><sup>2</sup> - P<sub>k</sub><sup>2</sup></li> <li>P<sub>c</sub><sup>2</sup> - P<sub>d</sub><sup>2</sup></li> <li>divided by: P<sub>c</sub><sup>2</sup> - P<sub>d</sub><sup>2</sup></li> </ol> | LOG of formula 1, or 2, and divide | formula<br>1, or 2,<br>and divide p.2. p.2 |   | Backpressure Curve Slope = "n" Assigned Standard Slope |                               | LOG   | Antilog                        | Deli<br>Equals | Open Flow<br>Deliverability<br>Equals R x Antilog<br>(Mcfd) |  |
|   |                          |   |  |   |                                    |  |   |  |                               |   |                                |                | <u>.</u>  |  |
|   |                          | _   |  |   |                                    |  | <u> </u>  |  | <u> </u>                      |   |                                |                |   |  |
| Open Flo  | <u>w</u>                 |   |  | Mcfd @ 14.  | 65 psia                            |  | Deliverabi  | lity   |                               | <del></del>   | Mcfd @ 14.65 psi               | a              |   |  |
|   |                          |   |  | n behalf of the<br>aid report is true   |                                    | t, Executed                                | this the 9  |  |                               | e above repo  | rt and that he ha              |                | ledge of<br><sub>20</sub> <u>15</u> .                       |  |
|   |                          |   | Witness (  | f anv)  | ı                                  | KANSAS CORP                                | PORATION COMI                                       | Missio   | ln l                          | P &   | Company Company                | <u>_</u> _     | _   |  |
|   |                          |   |  |   | <u></u>                            | <u> </u>                                   | 1 6 20 <u>1</u>                                     | 5  |                               |   |                                |                |   |  |
|   |                          |   | For Comm   | ission  |                                    | CONSERV                                    | ATION DRUGG   | ~~   |                               | Chec  | ked by                         |                |   |  |

CONSERVATION DIVISION WICHITA, KS

| exempt status und<br>and that the foreg<br>correct to the best<br>of equipment insta | er penalty of perjury under the laws of the state of Kansas that I am authorized to request er Rule K.A.R. 82-3-304 on behalf of the operator WOOLSEY OPERATING CO, LLC oing pressure information and statements contained on this application form are true and of my knowledge and belief based upon available production summaries and lease records illation and/or upon type of completion or upon use being made of the gas well herein named. Lest a one-year exemption from open flow testing for the JAHAY 5 |
|--|---|
|  | bunds that said well:   |
| •  | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No is not capable of producing at a daily rate in excess of 250 mcf/D to supply to the best of my ability any and all supporting documents deemed by Commission to corroborate this claim for exemption from testing.   |
| Date: 10/9/15  |   |
|  | Signature: Wind Skilland  |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.