

7-28-88

To: 1 051074
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-047-20,516-0000

SE, SE NE, SEC. 4, T 26 S, R 16 W/E

2970 feet from S section line

330 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5142

Lease Name Cudney "B" Well # 2-4

Operator: Sterling Drilling Company

County Edwards 147.23

Name & Address Box 129

Well Total Depth 4530 feet

Sterling, KS 67579

Conductor Pipe: Size feet

RECEIVED
STATE CORPORATION COMMISSION
SUMMER
AUG 4 1988
8-4-88

Casing: Size 8 5/8 feet 416

Abandoned Oil Well Gas Well ~~Adapt~~ Well SWD Well D&A

Other well as hereinafter indicated

Plugging Contractor Kelso Casing Pulling, Inc. License Number 6050

Address Box 347, Chase, KS 67524

Company to plug at: Hour: 12 p.m. Day: 28 Month: 7 Year: 19 88

Plugging proposal received from Bill Fulls

(company name) Kelso Casing Pulling, Inc. (phone) 316-938-2457

were: 4 1/2" at 4521' Perfs at 4438-42'

1st plug sand back to 4490' and dump 4 sx cement on top of sand through bailer,

2nd plug pump 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8" wiper plug and pump 120 sx cement.

Plugging Proposal Received by Richard Lacey (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 1 p.m. Day: 28 Month: 7 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug sanded back to 4490' and dumped 4 sx cement on top of sand through bailer,

2nd plug pumped 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, released 8 5/8" wiper plug and pumped 120 sx cement.

Maximum pressure 200 psi and shut in 50 psi.

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2300' of 4 1/2" casing. (If additional description is necessary, use BACK of this form.)

INVOICED

(If desired, XXXXXX) observe this plugging.

DATE 8-5-88

Signed Richard W. Lacey (TECHNICIAN)

INV. NO. 21780