


15-155-03062-0000

TABOR & COLEMAN
Mueller No. 1.

SEC. 25 T. 24 R. 5W
NE 1/4 SE

Total Depth. 3915'
Comm. 5-11-37 Comp. 8-8-37
Shot or Treated.
Contractor.
Issued. 10-2-37

County. Reno



CASING:
12 1/2" 548'
7 " 3368'
53/16" 3670' UR 3796'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

sand	160
sand & shells	360
sand, shale & shells	460
shale & shells	538
sand & shells	555
lime	775
shale & lime	865
brkn lime & shale	1000
brkn lime	1140
lime	1220
shale	1270
lime & shale	1365
shale & shells	1515
shale	2065
lime & shale	2140
lime brkn	2257
lime & shale	2345
shale	2430
shale & shells	2673
lime	2830
lime & shale	2888
lime	3140
shale & brkn lime	3180
lime	3389
sdv chat	3418
sdv lime	3428
lime	3435
sdv lime	3438
lime	3485
lime sh oil	3495
lime	3557
sdv lime good sh oil	3562
lime	3586
shale	3666
shale & shells	3670
lime-bailing wtr	3677
shale brown	3679
shale	3697
sand wtr	3698
sand	3704
shale	3706
Top Hunton 3707	
more wtr 3708-3710	
lime	3766
sdv shale	3775
lime	3781
sdv shale	3790
Top Viola 3797	
lime	3820
sand Wilcox	3847
lime	3859
sand	3894
lime	3901
shale	3905
lime	3915
Total Depth.	

PLUGGING
FILE SEC 25 T. 24 R. 5W
BOOK PAGE 107 LINE 1