

To: 1 030903
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

1-8-88
API NUMBER 15- 047-21,308-0000
NW SE SW, SEC. 2, T 26 S, R 18 (W/R)
990 feet from S section line
3630 feet from E section line
Lease Name Kathleen Ellinghaus 1
County Edwards 156.81
Well Total Depth 4825 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 604

TECHNICIAN'S PLUGGING REPORT

Operator License # 3536
Operator: Ramco Drilling Services, Inc.
Name &
Address Box 99
Belpre, Ohio 45714

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Red Tiger Drilling Company License Number 5302

Address 1720 Kansas State Bank Building, Wichita, KS 67202

Company to plug at: Hour: 7 a.m. Day: 8 Month: 1 Year: 19 88

Plugging proposal received from Pat Waggoner

(company name) Red Tiger Drilling Company (phone) 316-263-1201

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 2160' KB
Anhydrite 1230-52'

1st plug at 1230' with 50 sx cement, 2nd plug at 630' with 40 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Durrant
(TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 8:30 a.m. Day: 8 Month: 1 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug at 1230' with 50 sx cement,

2nd plug at 630' with 40 sx cement,

3rd plug at 40-0' with 10 sx cement,

4th plug to circulate rathole with 15 sx cement.

RECEIVED
STATE CORPORATION COMMISSION

JAN 11 1988 1-11-1988

CONSERVATION DIVISION
Wichita, Kansas

Remarks: Used 60/40 Pozmix 6% gel by Halliburton.
(if additional description is necessary, use BACK of this form.)

(I did not observe this plugging.)

INVOICED

Signed Steve Durrant
(TECHNICIAN)

DATE 1-13-88

INV. NO. 19561

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Expected Spud Date: 12-28 87 month day year

API Number 15-047-21,308-0002

OPERATOR: License # 3536 Name: Ramco Drilling Services, Inc. Address: Box 99 City/State/Zip: Belpre, Ohio 45714 Contact Person: Bob Williamson Phone: 614-423-9591

NW SE SW Sec. 2 Twp. 26 S, Rg. 18W East West 990 Ft. from South Line of Section 3630 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

Nearest lease or unit boundary line 990 feet County: Edwards

CONTRACTOR: License # 5302 Name: Red Tiger Drilling Co., 1120 Bldg. City/State: Wichita, Kansas 67202

Lease Name: Kathleen Ellinghaus Well # 1

Well Drilled For: Oil Storage Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

Ground surface elevation feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no

If OWWO: old well info as follows:

Depth to bottom of fresh water: Depth to bottom of usable water: 280 Surface pipe by Alternate: 1 A 2 Surface pipe planned to be set: 600 Conductor pipe required: N/A Projected Total Depth: 4850 Formation: ARB

Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., and the rules and regulations of the K.C.C. Date: 12-22-87 Signature of Operator or Agent: George A. Angle Title: Owner

For KCC Use: BY RED TIGER DRILLING CO. Conductor Pipe Required feet; Minimum Surface Pipe Required 300 feet per Alt. (1) X This Authorization Expires: 6-22-88 Approved By: P.H. 12-22-87

EFFECTIVE DATE: 12-27-87

Handwritten notes: 12-24-87

Handwritten notes: 3 3/8" 600' Paul

Handwritten initials: w/w

NW SE SW Sec. 2 Twp. 26 S, Rg. 18W East West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ft. deep: ARB or formation with: 50 SX feet of: 60-40 poz., 6% gel
2nd plug @ ft. deep: B ANH or formation with: 50 SX feet of:
3rd plug @ ft. deep: 630 or formation with: 40 SX feet of:
4th plug @ ft. deep: 40 or formation with: 10 SX feet of:
5th plug @ ft. deep: or formation with: feet of:
(2) Rathole to surface minus 5 feet 15 SX (b) Mousehole to surface minus 5 feet

Handwritten log: PUSHER Pat Wayner TD-48-25 FORMATION 4-8-88 SURFACE PIPE 8 7/8 @ 604 ANHYDRITE 1230 ELEVATION 216015 STARTING TIME & DATE 1-8-88 7:00 AM COMPLETION TIME & DATE 1-8-88 8:30 AM 1st PLUG @ 1230 FT. W/ 50 SX 2nd PLUG @ 630 FT. W/ 40 SX 3rd PLUG @ 40-0 FT. W/ 10 SX 4th PLUG @ FT. W/ SX RAT HOLE CIRCULATED W/ 15 SX MOUSE HOLE CIRCULATED W/ SX WATER WELL PLUGGED W/ P-T-B w/cut - Halliburton CEMENT COMPANY Halliburton TECHNICIAN S.D.

RECEIVED STATE COMPLETION COMMISSION JAN 11 1988 CONSERVATION DIVISION Wichita, Kansas