

1-24

To: 1 061179  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 047-20,125-~~606~~  
NW NE SW, SEC. 33, T 26 S, R 16 W  
2310 feet from S section line  
3630 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5414  
Operator: J. Mark Richardson  
Name  
Address 111 West Douglas, Suite 640  
Wichita, KS 67202

Lease Name Schultz Well # 1  
County Edwards 147.29  
Well Total Depth 4532 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 357

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Greensburg Well Service License Number \_\_\_\_\_

Address \_\_\_\_\_

Company to plug at: Hour: 10 a.m. Day: 24 Month: 1 Year: 19 89

Plugging proposal received from Carl Schield

(company name) J. Mark Richardson (phone) 316-723-2204

were: 4 1/2" at 4527' Open Hole

1st plug sand back to 4475' and dump 4 sx cement on top of sand through bailer,  
2nd plug pump 2 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, and 120 sx  
cement.

RECEIVED  
STATE CORPORATION COMMISSION

JAN 25 1989

Plugging Proposal Received by Paul A. Luthi  
(TECHNICIAN)

Plugging Operations Controlled by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 11 a.m. Day: 24 Month: 1 Year: 19 89

ACTUAL PLUGGING REPORT 1st plug sanded back to 4475' and dumped 4 sx cement on top of  
sand through bailer,  
2nd plug pumped 2 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, and 120 sx  
cement.

Maximum pressure 200 psi and shut in 150 psi.

Remarks: Used 60/40 Pozmix 6% gel by Halliburton. Recovered 1800' of 4 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

INVOICED

DATE 1-27-89

INV. NO. 23807

1-24

Signed Paul A. Luthi  
(TECHNICIAN)