SIDD ONL			·		an to
rado Derby B	nall be filed in dupl Building, Wichita, Kan Egardless of how the	nsas 67202, within well was completed.	ten days a	fter the co	mpletion of
confidential	eparate letter of requel, only file one copy it then be held confident	. Information on s			
Circle one: Applications	Oil, Gas, Dry, SWD, s must be filed for d freline logs (i.e. el	OWWO, Injection. !	mingling, SW	D and inject	ction, T.A.
KCC # (316)	263-3238. (Rules 8)	2-2-105 & 82-2-125)	rog, gamma	ray neutron	r log, etc.).
OPERATOR	Sterling Drilling	Company	API NO	15-047-20	963-000
ADDRESS	P. 0. Box 129		COUNTY	Edwards	
	Sterling, Kansas	67579	FIELD	Wil	· · · · · · · · · · · · · · · · · · ·
**CONTACT PE	ERSONOlin_Kelso		PROD. FORM	ATION Kin	derhook Sand
	PHONE 316-278-27	131	LEASE	Cudney "B	d.
PURCHASER	Getty Crude Gather:		. 2000		The same of the contraction of t
ADDRESS	P. O. Box 3000			8-4	
<del></del>	Tulsa, Oklahoma 74	4102			
DRILLING	Sterling Drilling (	Company			th Line and
CONTRACTOR ADDRESS	P. O. Box 129				Line of
	Sterling, Kansas (	57579		EC. <u>4</u> TWE LL PLAT	2-26S RGE 16
PLUGGING			*D		
CONTRACTOR		RECEIVED			KCC _
ADDRESS	·	STATE CORPORATION COMM	991-81		KGS(Office
<del></del>		1/26/87	-		Use)
TOTAL DEPTH_	4535† PB	CKDL O Z W VI'.		_	
	11-24-81 DATE COMPI	1.00/25/30/2000/05/15/1	OM		
ELEV: GR	2079 DF 2085	<u> Кв 2088</u>			-
DRILLED WITH	I (CABLE) ( <u>ROTARY</u> ) (A	IR) TOOLS	L		
Amount of su	irface pipe set and co	emented437.38'	. Dv	V Tool Used	1?No
		AFFIDAVI	<b>T</b>		
STATE OF	KANSAS	***************************************	•	SS.	I.
	F. A. Wuellner				_
DEPOSES THAT	HE IS Secretary	(FOR)	)(OF)STEF	RLING DRILI	LING COMPANY
	THE Cudney "B"				<u>-</u>
THIS AFFIDAV	IT FOR AND ON THE BEH	HALF OF SAID OPERATO	OR, THAT WELI	L NO <u>8-</u>	-4 ON
SAID LEASE H	IAS BEEN COMPLETED AS	OF THE 23rd DAY	OF Decembe	er, 19_	81_, AND THAT
ALL INFORMAT	CION ENTERED HEREIN WI	ITH RESPECT TO SAID	WELL IS TRUE	E AND CORRE	CT.
FURTHER AFFI	ANT SAITH NOT.	·	STERL	ING DRILLI	NG COMPANY
			(S) \Al	unce	en
SUBSCRIBED A	AND SWORN BEFORE ME TH	HIS 23rd DAY OF	FA	Wuellner	Secretary
AG S	NES D. WURST tate of Kansas		- Junua	Want	•, <u></u> •
MY COMMISSIO	NES D. WURST tate of Kansas LEXP. 4-6-85 ON EXPIRES: 4-6-85	Agnes D	. Wirst, NO	TARY PUBLIC	to the state of the same was a second and
	who can be reached !		- anv duéstion	a concernia	no this infor-

\*\*The person who can be reached by phone regarding any questions concerning this information. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.

			pan, flowing and	<del></del>	res, and recoveries.	Production of the second			N.
FORMATI	ION DESCRIPTION,	CONTENTS, ETC	<del></del>	ТОР	BOTTOM	A NAME	1 (A)	DEPTH	, 4 <sub>00</sub>
Drill Stem T	ests: Non	e run	÷ •		0.00	Gamma Ra	,	7. 50Ô ´	
,			•					4500	in Streen
	•					Acoustic Cement		,	
			,	,		Bond Log	1	4500	<u> </u>
ı			•	•				11	
	,								
·t									
	. •				,				
							j		
	,		•	j	· ·				
			•	J			, from Manage an	a a Epina a	n, etni kryva,
						1		•	
			,	1		14	· }		
								Ē.	
					<b>,</b>	. :			
•	,								
	•			ļ		}	4.		
•	'			<b>.</b>		<u> </u>	.,	,	• ,
	•		2	1			1		
								8	
	ā.			}	<u> </u>			14	' e .
				]		<b>)</b>	1		
Report of all string	gs set — surface,	intermediate,	production, et	c. CASING	RECORD (Net	w) or (Used			-
Purpose of string	Size hole drilled	Size casing set (In O.D.)	Weight lbs/ft.	Setting depth	Type cament	Sacks		nd percent ditives	<b>-</b> .
urface	12 1/4"	8 5/8"	23#	448'	(60 1/0 B				- % c∈
					60/40 Pozm	i <b>‡</b> 375	2% ge	1 and 3	
raduction	7 7/8"	4 1/2"	10.5#	4525'	Howco Lite	100		<del></del> :	<u>-</u>
roduction	7 7/8"	4 1/2"	10.5#	4525'	<del></del>	100	18% sa	1t. 3/4 5# gil:	soni
roduction	7 7/8"	4 1/2"	10.5#	4525'	Howco Lite	100	18% sa	1t, 3/4 5# gil: locele,	soni
			10.5#	4525'	Howco Lite 50/50 Pazmi	100 x 125	18% sa CFR-2, 1/8# f tuffib	1t, 3/4 5# gil: locele,	soni
	LINER RECOR			Shots p	Howco Lite 50/50 Pozmi PERFO	100	18% sa CFR-2, 1/8# f tuffib	1t, 3/4 5# gil: locele, er.	soni
	LINER RECOP	RD Sacks ce		Shots p	Howco Lite 50/50 Pozmi PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t, 3/4 5# gil: locele, er.	soni
n.	LINER RECOR	Sacks ce	iment	Shots p	Howco Lite 50/50 Pozmi PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t, 3/4 5# gil: locele, er.	soni
n.	LINER RECOR Bottom, ft. TUBING RECO Setting depth 4420 KB	Sacks ce	rment et at	Shots p	Howco Lite 50/50 Pozmi  PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t, 3/4 5# gil: locele, er.	soni
n.	LINER RECOR Bottom, ft. TUBING RECO Setting depth 4420' KB	Sacks ce  ORD  Packer to  ACID, FRACTL	et at	Shots p	Howco Lite 50/50 Pozmi PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t. 3/4 5# gil: locele. er.	soni
3/8"	LINER RECORD Bottom, ft.  TUBING RECORD Setting depth 4420 KB	Sacks ce  Sacks ce  Packer to  ACID, FRACTE  out and kind of in	et at URE, SHOT, C	Shots p	Howco Lite 50/50 Pozmi  PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib D Depth 4426	1t. 3/4 5# gil: locele. er.	soni
3/8"	LINER RECORD Bottom, ft.  TUBING RECORD Setting depth 4420 KB	Sacks ce  Sacks ce  Packer to  ACID, FRACTE  out and kind of in	et at URE, SHOT, C	Shots p	Howco Lite 50/50 Pozmi  PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t. 3/4 5# gil: locele. er.	soni
3/8" See attached	LINER RECORD Bottom, ft.  TUBING RECORD Setting depth 4420 KB	Sacks ce  Sacks ce  Packer to  ACID, FRACTE  out and kind of in	et at URE, SHOT, C	Shots p	Howco Lite 50/50 Pozmi  PERFO	100 125 RATION RECOR	18% sa CFR-2, 1/8# f tuffib	1t. 3/4 5# gil: locele. er.	soni
%. 3/8" See attached	LINER RECORD Bottom, ft.  TUBING RECORD Setting depth 4420 KB	Packer to ACID, FRACTION and kind of the Dan Report.	et at URE, SHOT, C	Shots p	PERFO PERFO PERFO	RATION RECOR	18% sa CFR-2, 1/8# f tuffib  D Depth 4426	1t. 3/4 5# gil: locele. er.  Interval - 30	soni
%. 3/8" See attached	LINER RECORD Bottom, ft.  TUBING RECORD Setting depth 4420 KB	Packer to ACID, FRACTION Report, Producing	et at URE, SHOT, C	Shots p	PERFO PERFO PERFO	RATION RECOR	18% sa CFR-2, 1/8# f tuffib  D Depth 4426	1t. 3/4 5# gil: locele. er.  Interval - 30	soni