AFFIDAVIT OF COMPLETION FORM (REV) ACO-1 SIDE ONE This form shall be filed in duplicate with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ten days after the completion of the well, regardless of how the well was completed. Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on side one will be of public record and side two will then be held confidential. Circle one: Oil, Gas, Dry, SWD, OWWO, Injection. Type and complete ALL sections. Applications must be filed for dual completion, commingling, SWD and injection, T.A. Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). T # (316) 263-3238. (Rules 82-2-105 & 82-2-125) KCC # (316) 263-3238. API NO. 15-047-20,974 -6000 OPERATOR Sterling Drilling Company ADDRESS P. O. Box 129 COUNTY Edwards Sterling, Kansas 67579 FIELD Wil PROD. FORMATION Kinderhook Sand **CONTACT PERSON Olin Kelso PHONE 316-278-2131 LEASE Cudney "B" PURCHASER Getty Crude Gathering, Inc. WELL NO.____9-4 ADDRESS P. O. Box 3000 WELL LOCATION Tulsa, Oklahoma 74102 1875 Ft. from North Line and DRILLING Sterling Drilling Company CONTRACTOR 990 Ft. from East Line of ADDRESS ____ P. O. Box 129 the NE/4 SEC. 4 TWP. 26S RGE. 16WSterling, Kansas 67579 WELL PLAT PLUGGING KCC KGS CONTRACTOR ADDRESS (Office Use) TOTAL DEPTH 4535' PBTD SPUD DATE 12-6-81 DATE COMPLETED 12-12-81 ELEV: GR _____ DF___ KB 2081' DV Tool Used?

VIT

RICE Wichits Kansas DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS Amount of surface pipe set and cemented 420.65 TATE CAMPAGE DV TOO AFFIDAVIT STATE OF KANSAS , COUNTY OF F. A. Wuellner OF LAWFUL AGE, BEING FIRST DULY SWORN UPON HIS OATH, DEPOSES THAT HE IS Secretary (FOR)(OF) STERLING DRILLING COMPANY Cudney "B" OPERATOR OF THE LEASE, AND IS DULY AUTHORIZED TO MAKE THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERATOR, THAT WELL NO . 9-4 SAID LEASE HAS BEEN COMPLETED AS OF THE 31st DAY OF December , 19 81 , AND THAT ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID WELL IS TRUE AND CORRECT. FURTHER AFFIANT SAITH NOT. STERLING DRILLING COMPANY (S) Dannien F. A. Wuellner, Secretary SUBSCRIBED AND SWORN BEFORE ME THIS 23rd DAY OF . January , 19 82 AGNES D. WURST State of Kansas My Appt. Exp. 4-6-9-1 egner S. Warst Agnes D Wurst NOTARY PUBLIC MY COMMISSION EXPIRES: 4-6-85

**The person who can be reached by phone regarding any questions concerning this information. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.

Sold

WELL LOG

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including death interval tested cushing used time tool open, flowing and shuf-in pressures and recognized.

CFPB

FORMATION DESCRIPTION, CONT			TOP		TTOM	NAME		DEPTH
Drill Stem Tests: None		,			,	Gamma Ra Neutron	У	4500
						Acoustic Cement B		4498
C.						Log	,	
Mr. t		•		in .	¥	e so disa in ini.		,
						•		· ·
<i>y</i>						••		
						e e e e e e e e e e e e e e e e e e e	i.*	
			}					
					~			
• • • • • • • • • • • • • • • • • • • •		4			m 7 · i 4 · 4	and the state of the second	n and it described	takanikan yan yan
					-	42 · ·		
•					* · ·		•	
					94 (24)		· ·	
•					'			
		°e.			!	e i		, 1
			ļ		1			,
1						u .	į	
						,		
]					
•			<u> </u>	ļ				
			}			· ·		
Report of all strings set — surface, inter		roduction, et	c. CASING	RECORD	(New) or (Used) F.E.	e
Purpose of string Size hale drilled Size	n O.D.)	Weight lbs/ft.	Setting dapth	Туре	ement	Sacks	Тур	e, and percent. additives
urface 12 1/4" 8	5/8"	}	433!_	60/40	Pozmi	x 375 *	2%	gel and 3% o
roduction 7 7/8" 4	1/2"	10.5#	45 27'	Howco		75	100	- 14 5"
				20/20	Pozmi	x 75	3/4	salt, 5# gil of 1% CFR-2,
							fibe	r, 1/8# floo
		l	-r -	<u></u>	· .		<u> </u>	** ** ***
t. Bottom, ft. Sacks cament						ATION RECORD		. <i>e</i> *
, n. Bottom, n.	Jacks cament			Shots per ft.		ize & type	Depth Interval 4420 - 24'	
TUBING RECORD			7				,	* *
Setting depth	Packer set	t ot:	1		- 	*		· · · · · · · · · · · · · · · · · · ·
3/8" 4412' K.B.	FRACTU	RE, SHOT, (CEMENT SO	UEEZE RF	ORD	·	L.	
	d kind of m				,	Dep	h Interv	ol treated
ee Completion Report (att	ached)			·		-		
,						- }		
<u> </u>								
e of first production						Tenum.		
of first production		Pumping	üğ, bambırd, i	es lift, etc.)	ب سواده به هم هم	- Fravito	or Erp.	IA YM STEEL THE

Water % RATE OF PRODUCTION PER 24 HOURS 30 Disposition of gas (vented, used on lease or sold) Perforations 4420 - 24