This form shall be filed in duplicate with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ten days after the completion of the well, regardless of how the well was completed. Attach separate letter of request if the information is to be held confidential . If confidential, only file one copy. Information on side one will be of public record and side two will then be held confidential. Circle one: Oil, Gas, Dry, SWD, OWWO, Injection. Type and complete ALL sections.

Applications must be filed for dual completion, commingling, SWD and injection, T.A.

Attach wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.).

KCC # (316) 263-3238. (Rules 82-2-105 & 82-2-125) API NO. 15-047-20,975-6960 OPERATOR Sterling Drilling Company ADDRESS P. O. Box 129 COUNTY Edwards Sterling, Kansas 67579 FIELD___ Wil **CONTACT PERSON Olin Kelso PROD. FORMATION Kinderhook Sand PHONE 316-278-2131 LEASE Cudney "B" PURCHASER Getty Crude Gathering, Inc. a section by proper consequences WELL NO. ADDRESS P. O. Box 3000 WELL LOCATION_____ Tulsa, Oklahoma 74102 990 Ft. from South Line and DRILLING Sterling Drilling Company CONTRACTOR 990 Ft. from East Line of ADDRESS P. O. Box 129 the NE/4 SEC. 4 TWP. 26S RGE. 16W Sterling, Kansas 67579 WELL PLAT PLUGGING KCC ___ CONTRACTOR · ADDRESS KGS (Office Use) TOTAL DEPTH 4550 PBTD_ SPUD DATE 12-15-81 DATE COMPLETED 12-21-81 ELEV: GR 2086' DF KB 2095' DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS DV_Tool/Used? Amount of surface pipe set and cemented____429.02' STATE COPPORATION COMMISSED 1/26/82 AFFIDAVIŢ STATE OF_ ____, COUNTY OF___ KANSAS RICE TAVATIONS SPICTAL F. A. Wuellner OF LAWFUL AGE, BEING FIRST DUEY SWORN UPON HIS OATH, DEPOSES THAT HE IS Secretary (FOR)(OF) STERLING DRILLING COMPANY OPERATOR OF THE Cudney "B" LEASE, AND IS DULY AUTHORIZED TO MAKE THIS AFFIDAVIT FOR AND ON THE BEHALF OF SAID OPERATOR, THAT WELL NO. 10-4 SAID LEASE HAS BEEN COMPLETED AS OF THE 9th DAY OF January , 1982 , AND THAT ALL INFORMATION ENTERED HEREIN WITH RESPECT TO SAID WELL IS TRUE AND CORRECT. FURTHER AFFIANT SAITH NOT. STERLING DRILLING COMPANY (S) Salley Con F. A. Wuellner, Secretary SUBSCRIBED AND SWORN BEFORE ME THIS 23rd DAY OF January , 19 82 State of Kansas My Appt. Exp. 4-4-8: equel D. Wart Agnes D. Wurst NOTARY PUBLIC

**The person who can be reached by phone regarding any questions concerning this information. Within 45 days of completion, a witnessed initial test by the Commission is required if the well produces more than 25 BOPD or is located in a Basic Order Pool.

MY COMMISSION EXPIRES: 4-6-85

Show all important zones of porosity and contents thereof; cored intervoluting depth interval tested, cushion used, time tool open, flowing and s	•		OR OTHER
FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	1 NA

	Tests: No	one	•		. ,		Gamma Ra Neutron	ıy	:4525	u· ·
							Acoustic Cement E		4526	* *
					1	l	Log	,		
2.48						*		,		
						[, .	6	~	*1
	* .							Į.		· ·
	· .			}		1,	e Cara			•
	•			1			T ₁	**		к.
			:	1						
``````````````````````````````````````	r en					e selene ný b	राज्यास्य १६३४ ज्योगसम्बद्धाः । स. स. ५	al a přímětogago	PMP (AMP IN APPEARLY SANS BASE FRANCE &	an or Figure
									٠	vi4 ,
			• .			1			į.	
;	<u>k</u>			d	1,			J		9 - <u>1</u>
						}		j		
	i			1		* .	•	٠.	· · · · · · · · · · · · · · · · · · ·	′ 、
•	:					}				
				İ						ė.
1	•					Ī		İ	•	
•				ļ				`		
				.]		}		1		
•						, ]		Í		•
,				ł		.		-	• · · · · · · · · · · · · · · · · · · ·	
·							<del></del>			_
Report of all strings	·		<del></del>		RECORD	(New	) or (Used	<del></del>		<b>-</b>
Purpose of string	Size hole drilled	Size casing set (in O.D.)	<del></del>	Setting depth	Туре с	ement	Sacks	Тур	e and percent additives	<del>-</del>
Purpose of string	·		<del></del>		Туре с 60/40	Pozmíx	\$acks 375	Тур	and percent additives el and 3%	- - - cc.
Purpose of string Surface	Size hole drilled	Size casing set (in O.D.)	<del></del>	Setting depth	60/40 Lite	Pozmíx - Howec	375 75	2% g	el and 3%	of 1%
Purpose of string Surface	Size hole drilled	Sixe casing set (in 0.b.)  8 5/8"	Weight lbs/ft.	Setting depth	60/40 Lite	Pozmíx	375 75	2% g 18% CFR-	el and 3% salt, 3/4 2; 5# gil	- _of 1% , 1/8#
Purpose of string Surface	Size hole drilled	Sixe casing set (in 0.b.)  8 5/8"	Weight lbs/ft.	Setting depth	60/40 Lite	Pozmix - Howec	375 75	2% g 18% CFR- ny10	el and 3%	of 1% , 1/8# 1/8# f
Purpose of string Surface Production	12 1/4" 7 7/8"	Size casing set (in 0.0.)  8 5/8"  4 1/2"	Weight lbs/ft.	Setting depth	60/40 Lite	Pozmix - Howec	\$acks 375 75 100	2% g 18% CFR- nylo seal	el and 3% salt, 3/4 2; 5# gil n fiber,	of 1% , 1/8# 1/8# f
Purpose of string Surface Production	Size hole drilled	Size casing set (in 0.0.)  8 5/8"  4 1/2"	Weight Ibs/H.	441 4548 h	60/40 Lite 50/50	Pozmix - Howeco	\$acks 375 75 100	2% g 18% CFR- nylo seal	salt, 3/4 2; 5# gil n fiber, per sack	of 1% , 1/8# 1/8# f
Purpose of string Surface Production	12 1/4" 7 7/8"	Size casing set (in 0.D.)  8 5/8"  4 1/2"	Weight Ibs/H.	Setting depth	Type c 60/40 Lite 50/50	Pozmix - Howeco	\$acks 375 75 100	2% g  18% CFR- nylo seal	el and 3% salt, 3/4 2; 5# gil n fiber,	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production	12 1/4" 7 7/8" LINER RECOR	Size casing set (in O.D.)  8 5/8"  4 1/2"  SQD  Sacks ce	Weight Ibs/ff.	Setting dapth 441 4548 1.	Type c 60/40 Lite 50/50	Pozmix - Howeco	\$acks 375 75 100	2% g  18% CFR- nylo seal	salt, 3/4 2; 5# gil n fiber, per sack	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production  O, ft. Bo	12 1/4" 7 7/8" LINER RECOR	Size casing set (in 0.D.)  8 5/8"  4 1/2"	Weight Ibs/ff.	Setting dapth 441' 4548'	Type c 60/40 Lite 50/50	Pozmix - Howeco	\$acks 375 75 100	2% g  18%  CFR- nylo seal	salt, 3/4 2; 5# gil n fiber, per sack	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production	12 1/4" 7 7/8" LINER RECOR	Size casing set (in O.D.)  8 5/8"  4 1/2"  SQD  Sacks ce	Weight Ibs/ff.  10,5	Setting dapth 441 4548 548 548 548 548 548 548 548 548 54	Type 6 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	\$acks 375 75 100	2% g  18%  CFR- nylo seal	salt, 3/4 2; 5# gil n fiber, per sack	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production	12 1/4" 7 7/8" LINER RECOR	Size casing set (in O.D.)	Weight Ibs/ff.  10.5	Setting dapth 441 4548 548 548 548 548 548 548 548 548 54	Type 6 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100 ATION RECOR	2% g  18%  CFR- nylo seal	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string Surface Production  , fr.   Bo	Size hole drilled  .12 1/4"  7 7/8"  LINER RECOR  attom, ft.  TUBING RECO  titing depth 4432 'KB  Amoun	Size casing set (in O.D.)  8 5/8"  4 1/2"  Sacks ce  RD  Packer se  CID, FRACTL  nt and kind of n	Weight Ibs/ff.  10.5  ment  TRE, SHOT, interiol used	Setting dapth 441 4548 548 548 548 548 548 548 548 548 54	Type 6 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100 ATION RECOR	2% g  18%  CFR- nylo seal	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string Surface Production  , tr.   50	Size hole drilled  .12 1/4"  7 7/8"  LINER RECOR  attom, ft.  TUBING RECO  titing depth 4432 'KB  Amoun	Size casing set (in O.D.)  8 5/8"  4 1/2"  Sacks ce  RD  Packer se  CID, FRACTL  nt and kind of n	Weight Ibs/ff.  10.5  ment  TRE, SHOT, interiol used	Setting dapth 441 4548 548 548 548 548 548 548 548 548 54	Type 6 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100 ATION RECOR	2% g  18%  CFR- nylo seal	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production  5. th. 5. 5.	Size hole drilled  .12 1/4"  7 7/8"  LINER RECOR  attom, ft.  TUBING RECO  titing depth 4432 'KB  Amoun	Size casing set (in O.D.)  8 5/8"  4 1/2"  Sacks ce  RD  Packer se  CID, FRACTL  nt and kind of n	Weight Ibs/ff.  10.5  ment  TRE, SHOT, interiol used	Setting dapth 441 4548 548 548 548 548 548 548 548 548 54	Type 6 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100 ATION RECOR	2% g  18%  CFR- nylo seal  Der 4444	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string Surface Production  5. #.   5.    2 3/8"   5.    See attached	12 1/4" 7 7/8" LINER RECOR	Size casing set (in O.D.)  8 5/8"  4 1/2"  Sacks ce  Packer w  CID, FRACTL  nt and kind of n  Report.	Weight Ibs/ff.  10.5  ment  et at  JRE, SHOT, ( material used	Setting depth 441 1 4548 1 Shots 4	Type c 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100  ATION RECOR	2% g 18% CFR- ny1o sea1  Det 4444	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production  5, ft.   Bo  3/8"  See attached	Size hole drilled  .12 1/4"  7 7/8"  LINER RECOR  Itlom, ft.  TUBING RECO  Itling depth  4432 KB  Amount  Completion	Size casing set (in O.D.)  8 5/8"  4 1/2"  Sacks case  Packer was called and kind of a Report.	Weight Ibs/ft.  10.5  The state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state	Setting depth 441 1 4548 1 Shots 4	Type c 60/40 Lite 50/50	Pozmix  Howed Pozmix  PERFOR	Sacks 375 75 100  ATION RECORD See & type  Deg  Cravition 36	2% g 18% CFR- nylo seal  Der 4444	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f
Purpose of string  Surface  Production  p, ft.   Bo	Size hole drilled  12 1/4"  7 7/8"  LINER RECOR  Hom, ft.  TUBING RECO  Hing depth 4432 KB  Amount  Completion	Size casing set (in O.D.)  8 5/8"  4 1/2"  RD  Sacks case  PRD  Packer was and kind of a Report.  Producing P	Weight Ibs/ft.  10.5  Innert  In State of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of the state of th	Setting depth 441' 4548' Shots 4 CEMENT SQL	Type c 60/40 Lite 50/50	Pozmix  Howed  Pozmix  PERFOR	Sacks 375 75 100  ATION RECORD See & type  Deg  Cravition 36	2% g  18% CFR- ny1o seal  AD  Dep 4444	el and 3% salt, 3/4 2; 5# gil n fiber, per sack oth interval 0 - 44	of 1% , 1/8# 1/8# f