

To: 1 051811 5-18  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION App.  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API-NUMBER 15-  
SE NE SW, SEC. 25, T 25 S, R 33  
1650 feet from S section line  
2970 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5952  
Operator: Amoco Production Co.  
Name:  
Address: 2225 W. Oklahoma Ave.  
Ulysses, KS 67880

Lease Name Murphy Well # 1  
County Finney 88.59  
Well Total Depth 2726 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 500

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Halliburton License Number \_\_\_\_\_  
Address \_\_\_\_\_

Company to plug at: Hour: 1 p.m. Day: 18 Month: 5 Year: 1994

Plugging proposal received from Richard Jenish  
(company name) Amoco Production Co. (phone) 316-356-1237

Work: 5 1/2" at 2572', cement circulated, PBD 2295', Liner-4 1/2"=2566-2726', Perfs at 2566-2726'  
1st plug set CIBP at 2495' with 2 sx cement on top,  
2nd plug circulate cement from 900' to 5'.

Plugging Proposal Received by Steve Durrant  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_  
Operations Completed: Hour: 2 p.m. Day: 18 Month: 5 Year: 1994

ACTUAL PLUGGING REPORT 1st plug set CIBP at 2495' with 2 sx cement on top,  
2nd plug mud to 900', ran tubing to 900' and circulated cement to surface.

Remarks: Used Class H cement by Halliburton. No casing recovery.  
If additional description is necessary, use BACK of this form.  
I (did / ~~XXXXXX~~) observe this plugging.

INVOICED

DATE 5-25-94

WV. NO. 40472

5-18

AUG 11 1994

Signed Richard W. Lacy  
RECEIVED  
STATE CORPORATION COMMISSION  
MAY 23 1994  
CONSERVATION DIVISION  
Wichita, Kansas