


TO  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION  
800 Bitting Building  
Wichita, Kansas



11-22-38

File 41-28

Abandoned oil well.

Location NW NW NW

Sec 25 Twp 24 Rge. 8 W

I have today completed supervision of plugging of:

Well No. 2 Lease Erasmus

Operator J. L. Dustin Address Culberson Nebraska

Field Perryville County Perry

Total Depth 3549' Feet. Started Plugging 11-10-38

(Describe briefly the manner in which well was plugged)

Cells and hole cemented. Bottom of hole  
from 3549' to 15' above N.C. Zone to 3507'  
Filled with heavy mud between plugs  
from 3507' to top of hole.  
Plugs rock 15' cement below base water  
at 360'. Plug rock 10' cement at base of cellar

Expense incurred as follows:

Date <u>11-10-38</u> *Day <u>1/4</u>	Mileage <u>61</u>	⑥
Date <u>11-12-38</u> *Day <u>1/4</u>	Mileage <u>45</u>	
Date <u>11-14-38</u> *Day <u>25 24 8 1/4</u>	Mileage <u>50</u>	
Hotel, meals, etc <u>11-16-38</u> \$ <u>40</u>		
<u>11-18-38</u> \$ <u>38</u>		
*Show as 1/4 - 23 1/4, or 4/4.		
<u>11-21-38</u> \$ <u>50</u>		

P. O. Erasmus Kansas Date 11-21-38  
1/2  
Guy W. [Signature]  
Conservation Agent


Mr J. L. Dustin, In Charge, Culberson  
Nebraska.

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.  
412 Union National Bk Bldg., Wichita, Kansas.

15-155-03095-00-00


T.S. DUSTIN ET AL  
Evans No. 2.

SEC. 25 T. 24 R. 8W  
NW NE NW



Total Depth. 3549'  
Comm. 4-2-37 Comp. 5-29-37  
Shot or Treated.  
Contractor. John F. Duwe  
Issued. 7-10-37

County. Reno



CASING:

15 1/2"	54-11	6"	3190'
12 1/2"	645	53/16"	3522'
10 "	2180		
8 1/2"	2720		

Elevation.

Production. Pot. 316 B.

Figures Indicate Bottom of Formations.

cellar	20	lime	2045
sand	60	shale & shells	2070
red rock	260	lime	2095
shale blue	270	shale blue	2105
red rock	365	lime	2115
shale grey	375	shale blue	2145
shale brown	385	shale grey	2175
shale grey	470	lime	2180
red rock	525	shale	2215
shale grey	580	shale blue	2240
shale blue	635	shale	2280
shale blue	720	lime	2290
salt & shale	755	shale blue	2310
salt	1155	lime	2320
shale	1160	shale	2340
lime	1185	lime	2365
shale & shells	1195	shale	2375
lime	1240	lime white	2440
shale blue	1260	shale	2520
lime	1280	lime	2595
shale grey	1285	shale	2650
lime	1310	lime	2680
shale grey	1320	sand	2690
lime	1365	HFV 2680-90	
shale blue	1370	lime	2720
lime	1375	lime brown	2955
shale grey	1380	HFV 2930	
lime	1405	slate	2975
red rock	1420	lime	3000
Ft. Riley	1455	shale	3020
lime	1500	lime	3065
1/2 BW 1480-90		shale blue	3100
1/2 BW 1558		sand	3168
brkn lime	1555	shale drk	3170
wtr sand	1560	lime	3195
lime	1587	lime	3430
red rock	1590	shale sdy	3440
lime	1600	lime	3505
shale blue	1610	black	3522
lime	1620	lime	3537
shale blue	1625	lime sft	3546
lime	1635	lime hrd	3549
sdv lime	1655	Total Depth.	
shale blue	1660		
lime	1680	500' oil in hole at 3537	
red rock	1685		
lime	1695		
shale grey	1705		
shale blk	1710		
lime	1775		
shale	1785		
lime	1810		
shale blue	1820		
lime	1845		
red rock	1855		
lime hrd	1915		
shale	1935		
lime	1985		
shale blue	1995		

