

1 060394

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 057-20,392-6000

SW NW , SEC. 2 ; T 26 S, R 21 W/E

3300 feet from S section line

4550 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 9726

Lease Name R. Wetzel Well # 1

Operator: Gruss Petroleum Management, Inc.
Name & Address 900 Building of the Southwest
Midland, TX 79701

County Ford 155.77

Well Total Depth 4793 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 483

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Cheyenne Drilling License Number 5382

Address Box 916, Garden City, KS 67846

Company to plug at: Hour: 2:00 pm Day: 8 Month: November Year: 19 84

Plugging proposal received from Gary Johnson

(company name) Cheyenne (phone) 316-277-2062

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 1350' with 50 sx cement

2nd plug at 510' with 50 sx cement
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement

5th plug to circulate rat hole with 10 sx cement

6th plug to circulate mouse hole with 10 sx cement

Plugging Proposal Received by Paul A. Luthis (TECHNICIAN)

Plugging Operations attended by Agent?: All X Part None

Operations Completed: Hour: 5:35 pm Day: 8 Month: November Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 1350' with 50 sx cement, 2nd plug at 510' with 50 sx cement, 3rd & 4th plugs -solid bridge - hulls - plug at 40' -- cement to surface with 10 sx cement, 5th plug to circulate rat hole with 10 sx cement, 6th plug to circulate mouse hole with 10 sx cement.

RECEIVED STATE CORPORATION COMMISSION

Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburton.
(if additional description is necessary, use BACK of this form.)

NOV 15 1984 11 15 84

CONSERVATION DIVISION Wichita, Kansas

Signed Paul A. Luthis (TECHNICIAN)

INVOICED
DATE 12-3-84
INV. NO. 5742