

To: 1090338 10-7  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 057-20,520-0000  
APP. NE SW NE, SEC. 5, T 26 S, R 21 W X  
1700 feet from N/S section line  
1480 feet from E section line

TECHNICIAN'S PLUGGING REPORT  
Operator License # 6412  
Operator: Sid Tomlinson  
Name & Address: 1802 Wildwood Dr.  
Stillwater, OK 74075

Lease Name Klenke Well # 1  
County Ford  
Well Total Depth 4890- 158.92 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 415

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor L.D. Drilling, Inc. License Number 6039  
Address RR 1, Box 183 B, Great Bend, KS 67530

Company to plug at: Hour: 9:30 p.m. Day: 7 Month: 10 Year: 19 93

Plugging proposal received from Bessie  
(company name) L.D. Drilling (phone) 316-793-3051

was: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1406'  
1st plug at 1400' with 50 sx cement, 2nd plug at 700' with 40 sx cement,  
3rd plug at 435' with 50 sx cement, 4th plug at 40' with 10 sx cement,  
5th plug to circulate rathole with 15 sx cement.

Plugging Proposal Received by Steve Middleton  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 12 p.m. Day: 7 Month: 10 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug at 1400' with 50 sx cement,  
2nd plug at 700' with 40 sx cement,  
3rd plug at 435' with 50 sx cement,  
4th plug at 40' with 10 sx cement,  
5th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Allied.

INVOICED

DATE / did not) observe this plugging.

INV. NO. 39026

Signed [Signature] (TECHNICIAN)

RECEIVED STATE CORPORATION COMMISSION  
OCT 1 1993  
RECEIVED CONSERVATION DIVISION  
OCT 1 1993  
STATE CORPORATION COMMISSION  
Wichita