

2-3-88

1051004

API NUMBER 15-047-20,302-6600

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION C S/2 S/2 SE, SEC. 18, T 26 S, R 17 W/EX  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

330 feet from S section line  
1320 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 6033  
Operator: Murfin Drilling Company  
Name & Address: 250 North Water, Suite 300  
Wichita, KS 67202

Lease Name Myers B Well # 1-18  
County Edwards 151.81  
Well Total Depth 4671 feet  
Conductor Pipe: Size \_\_\_\_\_ feet  
Surface Casing: Size 8 5/8 feet 282

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Kelso Casing Pulling License Number 6050

Address Box 347, Chase, KS 67524

Company to plug at: Hour: 11 a.m. Day: 3 Month: 2 Year: 19 88

Plugging proposal received from Mark McCabe

(company name) Kelso Casing Pulling (phone) 316-938-2457

were: 4 1/2" at 4660' PBSD 4613' Perfs at 4543-45, 4533-41'

1st plug sand back to 4475' and dump 4 sx cement on top of sand through bailer,

2nd plug pump 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8" wiper plug and pump 125 sx cement.

Plugging Proposal Received by Paul Luthi (TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 1 p.m. Day: 3 Month: 2 Year: 19 88

ACTUAL PLUGGING REPORT 1st plug sanded back to 4475' and dumped 4 sx cement on top of sand through bailer,

2nd plug pumped 4 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, released 8 5/8" wiper plug and pumped 125 sx cement.

STATE CORPORATION COMMISSION

Maximum pressure 300 psi and shut in 100 psi.

FEB 09 1988  
2-9-88

Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2400' of 4 1/2" casing.  
(if additional description is necessary, use BACK of this form.)

INVOICED

(if applicable) observe this plugging.

Signed Richard W. Lacey (TECHNICIAN)

DATE 2-10-88

INV. NO. 19809