STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUBGING SECTION CONSERVATION DIVISION - PLUBGING SECTION CONCERNATION DIVISION - PLUBGING SECTION COLORADO GERBY BUILDING WICHITA, MANSAS 67202  TECHNICIAN'S PLUGGING REPORT  Operator: RAMA Operating Co., Inc. County Stafford  Mansat Addrass P.O. Box 159  Stafford, KS 57578  Conductor Pipe: Size Surface Cosing: Size 8 5/8 foot 338  Abandonad GII Well X Gas Well laput Well SND Well OBA Other well as hereinaffer indicated Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529  Addrass P.O. Box 209, Chase, KS 67524  Company to plug ati Hour: 3:30 p.m. Day: 15 Month: 12 Year:19 94  Plugging proposel received from Hanny Boatwright (caspeny mand) Mike's Testing & Salvage Inc. License Number 3169-938-2943  Wers: 5½" at 4528' w/200 sx cement, Perfs at 4266-67, 4213-22'  Ist plug sand back to 4215' and dump 5 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 10 ex gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  Winer plug and pump 100 sx cement  PECEVER MANSASO  Operating Operations attended by Agent?: All X Part None  Operations of the Salvage Inc. Plugging Operations attended by Agent?: All X Part None Operations of the Salvage Inc. Company Testing Base attended by Agent?: All X Part None Operations of the Salvage Inc. Company Decay D	To:	1040922 12-15	API NUMBER 15- 185-22,249-0000
TECHNICIAM'S PLUGGING REPORT  Operator License / 3911  Operator: RAMA Operating Co., Inc.  Operator: RAMA Operating Co., Inc.  Stafford, KS 67578  County Stafford  Stafford, KS 67578  Conductor Pips: Size test  Surface Casing: Size 8 5/8 feet 338  Abandoned Oli Well X Gas Well imput Well SMD Well D&A  Other well as hereinafter indicated  Plugging Contractor Mike's Testing 6 Salvage Inc.  License Number 31529  Address P.O. Box 209, Chase, KS 67524  Coappany to plug at: Hour: 3130 p.m. Day: 15 Nonth: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (coapany neas) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  were: 5k" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  list plug sand back to 4215' and dump 5 sx cement on top of sand through batler,  2nd plug pump 3 ax hulls, 10 sx gel, 50 sx cemenc, 10 sx gel, 1 sx hulls, release 8 5/8"  winer plug and pump 100 sx cement.  PECCINED  Plugging Operations attended by Agent?: All X Part None  Operations of the Company and pump batler,  2nd plug pumped down 8 5/8" with 300 lbs, hulls, 10 sx gel, 50 sx cement on top of sand bridge through batler,  2nd plug pumped down 8 5/8" with 300 lbs, hulls, 10 sx gel, 50 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2500' of 5%" casing.  (If additional description is necessary, use 84cK of this fore)  (If additional description is necessary, use 84cK of this fore)	CONSERVA	TION DIVISION - PLUGGING SECTION	C NE SE , SEC. 11 , T 25 S, R 15 1
Operator Licenso / 3911  Stafford Name  Address P.O. Box 159  Abandoned Oli Well X Gas Well Input Well Study Well feet Surface Casing: Size 8 5/8 feet 338  Abandoned Oli Well X Gas Well Input Well SWD Well D&A  Other well as hereinafter Indicated Plugging Contractor Mike's Testing & Salvage Inc.  Address P.O. Box 209, Chase, KS 67524  Company to piug at: Hour: 3:30 p.m. Day: 15 Noath: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company asso) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  vere: 5th at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  ist plug sand back to 4215' and dump 5 sx cement on top of sand through badler, 2nd plug pump 3 sx hulls, 10 sx kel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  PEC 19 1994  Plugging Operations attended by Agent7: All X Port None  Operation Operations attended by Agent7: All X Port None  Operation Operations attended by Agent7: All X Port None  Operation Operations attended by Agent7: All X Port None  Operation Operations attended by Agent7: All X Port None  Operation of the plug sand back to 4200' and dumped 5 sx cement on top of sand bridge through bailor,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 osi.			1980 feet from S section i
Operator: RAMA Operating Co., Inc.  Operator: RAMA Operating Co., Inc.  Name: P.O. Box 159  Stafford, KS 67578  Conductor Pipe: Size foot  Surface Casing: Size 8 5/8 foot 338  Abandoned Oil Well X Gas Well input Well SWD Well Odd  Other well as hereinaffer indicated  Plugging Contractor Mike's Testing & Salvage Inc.  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 3:30 p.m. Day: 15 Month: 12 Year: 19 94  Plugging proposal received from Manny Bostwright  (company name) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  **Plugging Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  Operations operations attended by Agent?: All X Part None  Operations Operations attended by Agent?: All X Part None  (TECHNICIAN)  Plugging pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wipex plug and pumped 100 sx cement.  Maximum pressure 400 pei and shut in 50 psi.	TECHNICIA	AN'S PLUGGING REPORT	test from E section i
Operator: RAMA Operating Co., Inc.    County   Stafford		·	Lease Name Wilson Well # A-1
Name Address P.O. Box 159 Well Total Depth 4529 147.19 too  Stafford, KS 67578 Conductor Pipe: Size teet  Surface Casing: Size 8 5/8 fact 338  Abandoned Cli Well X Gas Well Input Well SWD Well DAA  Other well as hereinafter Indicated  Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 3:30 p.m. Day: 15 Month: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Ync. (phone) 316-938-2943  vera: 5½" at 4528" w/200 sx cement, Perfs at 4264-67, 4215-22"  1st plug sand back to 4215" and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  PECEIVED DAMMOSSON  (ANSIS COMPANATOR Of Depth Address attended by Agent?: All X Part None  Plugging Operations attended by Agent?: All X Part None  Operations of Depth Agent Chase State Hour: 4 p.m. Day: 15 Month: 12 Year:19 94  ACTUAL Plugging REPORT 1st plug sanded back to 4200" and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  (If additional description is necessary, use BACK of this form.)  (If additional description is necessary, use BACK of this form.)			
Stafford, KS 67578  Surface Casing: Size 8 5/8 fact 338  Abandoned Oil Well X Gas Well input Well SWD Well D&A  Other well as hereinafter Indicated  Plugging Contractor Mike's Testing & Salvage Inc. License Number 31529  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 3:30 p.m. Day: 15 Month: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  DEC VER Plugging Operations attended by Agent?: All X Part None  Operation of North Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  actual Plugging Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  Maximum pressure 400 psi and shut in 50 psi.  (1f additional description is necessary, use BACK of this form.)  (1g additional description is necessary, use BACK of this form.)	Name&		
Surface Casing: Size 8 5/8 fact 338  Abandoned Oli Well X Gas Well Input Well SYD Well D&A  Other well as hereinafter Indicated  Plugging Contractor Mike's Testing & Salvage Inc.  Address P.O. Box 209, Chase, KS 67524  Company to ping at: Hour: 3:30 p.m. Day: 15 Honth: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company nears) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  lst plug sand back to 4215' and dump 5 sx cement on top of sand through batler,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  winer plug and pump 100 sx cement.  RECEIVED  DEC 19 1994  Plugging Proposal Received by Richard Lacey  Open 19 1994  ACTUAL Plugging Operations attended by Agent?: All X Pert None  Open 19 1994  ACTUAL Plugging REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through batler,  2nd plug pumped down 8 5/8" with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 1bs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (11 additional description is necessary, use SACK of this form.)  INMO STATES Deserve this plugging.	Address	•	
Other veil as hereinafter Indicated  Plugging Centractor Mike's Testing & Salvage Inc.  License Number 31529  Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 3:30 p.m. Day: 15 Month: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  Ist plug sand back to 4215' and dump 5 sx cement on top of sand through batler,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8.5/8"  wiper plug and pump 100 sx cement.  2PCEIVED AND SOUND OF Plugging Proposal Received by Richard Lacey  DEC 19 1994  DEC 19 1994  Plugging Proposal Received by Richard Lacey  OFFICE AND SOUND OF STAND		Starroid, KS 07576	· ·
Other veil as hereinafter Indicated  Plugging Contractor Mike's Testing & Salvage Inc.  Address P.O. Box 209, Chase, KS 67524  Company to ping at: Hour: 3:30 p.m. Day: 15 Month: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8:5/8"  winer plug and pump 100 sx cement.  PECENED  PLUGGING OPPORTURED ON SUMSION  ANSAS COMPONENTIAL COMMISSION  PLUGGING OPPORTURED ON STITUTE HOURS ATTENDED ON STITUTE HOURS ATTEN		<del></del>	Surface Casing: Size 8 5/8 feet 338
Address P.O. Box 209, Chase, KS 67524  Company to plug at: Hour: 3:30 p.m. Day: 15 Honth: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  Ist plug sand back to 4215' and dump 5 sx cement on top of sand through bailer, 2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8-5/8"  wiper plug and pump 100 sx cement.  PECTIVED  DEC 19 1994  Plugging Proposal Roceived by Richard Lacey  Plugging Operations attended by Agent?: Al! X Part None  Operation Address Hour: 4 p.m. Day: 15 Honth: 12 Year:19 94  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement.  Maximum pressure 400 psi and shut in 50 psi.	Abandone	d Oli Well X Gas Well	Input Well SWD Well D&A
Company to plug at: Hour: 3:30 p.m. Day: 15 Nonth: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  winer plug and pump 100 sx cement.  **RECEIVED**  **DEC 19 1994*  **Plugging Proposal Received by Richard Lacey  Plugging Operations attended by Agent?: All X Part None  **Operation**  **Operation**  **Operation**  **Operation**  **Pungling Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  **Maximum pressure 400 psi and shut in 50 psi.**  **Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)  **Pungling Proposal Received 15 plugging.**	Other we	li as hereinafter Indicated	<del></del>
Company to plug at: Hour: 3:30 p.m. Day: 15 Nonth: 12 Year:19 94  Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  winer plug and pump 100 sx cement.  **RECEIVED**  **DEC 19 1994*  **Plugging Proposal Received by Richard Lacey  Plugging Operations attended by Agent?: All X Part None  **Operation**  **Operation**  **Operation**  **Operation**  **Pungling Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  **Maximum pressure 400 psi and shut in 50 psi.**  **Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)  **Pungling Proposal Received 15 plugging.**	Plugging	Contractor Mike's Testing & Salvage	License Number 31529
Plugging proposal received from Manny Boatwright  (coapeny neas) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  Ist plug sand back to 4215' and dump 5 sx cement on top of sand through batler,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  PECEIVED  DEC 19 1994  Plugging Proposal Received by Richard Lacey  Technician)  Plugging Operations attended by Agent?: All X Part None  Operation On None Communication attended by Agent?: All X Part None  Operation Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through batler,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use 9ACK of this form.)		•	·
Plugging proposal received from Manny Boatwright  (company name) Mike's Testing & Salvage Inc. (phone) 316-938-2943  vere: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  1st plug sand back to 4215' and dump 5 sx cement on top of sand through batler,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  winer plug and pump 100 sx cement.  **RECEIVED**  DEC 19 1994  **Plugging Operations attended by Agent?: All X Part None  Operation Operations attended by Agent?: All X Part None  Operation Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of  sand bridge through batler,  2nd plug pumped down 8 5/8" with 300 1bs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 1bs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use 9ACK of this form.)  December 10 systems 10 sy	Company	to plug at: Hour: 3:30 p.m. Day:	15 Month: 12 Year: 19 94
(company name) Mike's Testing & Salvage Inc.  (phone) 316-938-2943  were: 5½" at 4528' w/200 sx cement, Perfs at 4264-67, 4215-22'  Ist plug sand back to 4215! and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  **RECEIVED**  (ANSAS CORPUMATION DIVISION**  Plugging Operations attended by Agent?: All X Part None  Operations attended by Agent?: All X Part None  Operations attended by Agent?: All X Part None  Operations Division*  Operations attended by Agent?: All X Part None  Operations Division*  Operations attended by Agent?: All X Part None  Operations Division*  Operations attended by Agent?: All X Part None  Operations attended by Agent?: All X Part None  Operations Division*  Operations attended by Agent?: All X Part None  Operations Division*  None  Operations attended by Agent?: All X Part None  Operations Division*  None  Operations Agent None  Operations attended by Agent?: All X Part None  Operations Division*  None  Operations Agent None  Operations Agent None  Operations Agent None  Operations Division  None  Operations Division  Operations Agent None  Operations Agent None  Operations Agent None  Operations Division  None  Operations Division  Operations Agent None  Operations Division  Operations Division  Operations Agent None  Operations Division  Operations Division  Operations Agent None  Operations Division  Operat			
Ist plug sand back to 4215! and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  **RECEIVED MINISTON*  (ANSAS CORPURATION DIVISION*  Plugging Proposal Received by Richard Lacey  (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Operation Division*  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			
Ist plug sand back to 4215! and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  PECENTED  ANNSAS CORPURATION DIVISION  Plugging Proposal Received by  Richard Lacey  (TECHNICIAN)  Plugging Operations attended by Agent?: Al! X Part None  Operation Division plotted: Hour: 4 p.m. Day: 15 Month: 12 Year: 19 94  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			
Ist plug sand back to 4215! and dump 5 sx cement on top of sand through bailer,  2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  **RECENTED**  **Plugging Proposal Received by Richard Lacey  **TECHNICIAN)  **Plugging Operations attended by Agent?: Al! X Part None  **Open open open open open open open open o	were:5	$\frac{1}{2}$ " at 4528' w/200 sx cement, Perfs	at 4264-67, 4215-22'
2nd plug pump 3 sx hulls, 10 sx gel, 50 sx cement, 10 sx gel, 1 sx hulls, release 8 5/8"  wiper plug and pump 100 sx cement.  PECENTED  ANNAS CORPURATION COMMISSION  ANNAS CORPURATION DIVISION  Plugging Operations attended by Agent?: Al! X Part None  Operation Division None  Operation Division Before Hour: 4 p.m. Day: 15 Month: 12 Year:19 94  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			••
wiper plug and pump 100 sx cement.  PECEIVED  ANSAS CORPURATION COMMISSION  ANSAS CORPURATION COMMISSION  DEC 19 1994  Plugging Proposal Received by Richard Lacey  (TECHNICIAN)  Plugging Operations attended by Agent?: All X Part None  Open SENATION DIVISION  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			
RECEIVED  (ANSAS CORPUNATION COMMISSION  DEC 19 1994  Plugging Proposal Received by Richard Lacey  (TECHNICIAN)  Plugging Operations attended by Agenti: All X Part None  Operation Division  Operation Division  Actual Plugging Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel,  100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	<del></del>		
Plugging Proposal Received by Richard Lacey  DEC 19 1994  Plugging Proposal Received by Richard Lacey  (TECHNICIAN)  Plugging Operations attended by Agent?: Al! X Part None  Operation Division  Operations Division  Operations attended by Agent?: Al! X Part None  Operation Division  Operations attended by Agent?: Al! X Part None  Operation Division  Operations attended by Agent?: Al! X Part None  Operation Division  None  Operation Division  None  Operation Division  Operations attended by Agent?: Al! X Part None  Operation Division  None  Operation Division  Operations attended by Agent?: Al! X Part None  Operation Division  None  None  None  Operation Division  None  Operation Divisio			<u> </u>
Plugging Operations attended by Agent?: Al! X Part None  Operation Division attended by Agent?: Al! X Part None  Operation Division attended by Agent?: Al! X Part None  Operation Division Report 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	PECE	ION COMMISSION	
Plugging Operations attended by Agent?: All X Part None  Operation Division None  Operation None  Operatio	(ANSAS CURFORM	2-19-94 Plugging Prope	sal Roceived by Richard Lacey
Plugging Operations affended by Agenti: All X Part None  Operation DIVISION DAY: 15 Month: 12 Year:19 94  ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	nec 1	9 122.	( I COM TO TAR)
ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	Plugging	Operations attended by Agent?: A	I None
ACTUAL PLUGGING REPORT 1st plug sanded back to 4200' and dumped 5 sx cement on top of sand bridge through bailer,  2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	OPERVERV	ATION DIVINO DAY: 4 P.m. Day:	15 Month: 12 Year: 19 94
2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			
2nd plug pumped down 8 5/8" with 300 lbs. hulls, 10 sx gel, 50 sx cement, 10 sx gel, 100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)	, s		
100 lbs. hulls, released 8 5/8" wiper plug and pumped 100 sx cement.  Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)		<del></del>	
Maximum pressure 400 psi and shut in 50 psi.  Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)			
Remarks: Used 60/40 Pozmix 6% gel by Allied. Recovered 2600' of 5½" casing.  (If additional description is necessary, use BACK of this form.)  [Note: The state of the state o	100 1bs.	hulls, released 8 5/8" wiper plug	ind pumped 100 sx cement.
(If additional description is necessary, use BACK of this form.)  [Note 1] [Note 2] [Note 2] [Note 2] [Note 3]	Maximum	pressure 400 psi and shut in 50 psi	·
(If additional description is necessary, use BACK of this form.)  [National description is necessary, use BACK of this form.)  [National description is necessary, use BACK of this form.)			
(If additional description is necessary, use BACK of this form.)  [National description is necessary, use BACK of this form.)  [National description is necessary, use BACK of this form.)		Used 60//0 Pozmiy 6% gol by Allie	d Pacayarad 2600' of 5k" areing
INd O drawn this plugging.	Remarks	(If additional description is	necessary, use BACK of this form.)
	I NO AL		
DATE 1-5-73 FORM CP-2/			Signed Steel of The
FORM CP-2/	DATE	-5-75	(TECHNICIAN)
		41966	FORM CP-