

To: 1 020703 8-30
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

15-055-10075-00-00
APT NUMBER 15- Drill Completion Date 1/12/60

C SW NW, SEC. 32, T 26 S, R 34 W/E

3300 feet from S section line

660 feet from W/E section line

Lease Name USA Well # 12

(Was PPU #39) County Finney

Well Total Depth 5269 171.24 feet

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 805

TECHNICIAN'S PLUGGING REPORT

Operator License # 5293

Operator: Helmerich & Payne, Inc.

Name:

Address P.O. Box 558

Garden City, KS 67846

Abandoned Oil Well ☒ Gas Well ☐ Input Well ☐ SWD Well ☐ D&A ☐

Other well as hereinafter indicated

Plugging Contractor Helmerich & Payne, Inc. License Number 5293

Address P.O. Box 558, Garden City, KS 67846

Company to plug at: Hour: 11:30 a.m. Day: 30 Month: 8 Year: 19 93

Plugging proposal received from James Ford

(company name) Helmerich & Payne, Inc. (phone) 316-276-3693

Perfs: 5 1/2" at 5268' w/650 sx cement, Perfs at 4061-68, 5046-50, 5132-46, 5206-18', DV tool at

1st plug set CIBP at 4000' with 2 sx cement on top, PBTD 5229' 2809'

2nd plug spot plug at 2870-2970' with dump bailer,

3rd plug perforate at 900' with 175 sx cement.

Plugging Proposal Received by Case Morris
(TECHNICIAN)

Plugging Operations attended by Agent?: All ☐ Part ☐ None ☒

Operations Completed: Hour: 8:30 p.m. Day: 30 Month: 8 Year: 19 93

ACTUAL PLUGGING REPORT 1st plug set CIBP at 4000' with 4 sx cement on top,

2nd plug spot 100' plug at 2859-2759' with bailer-12 sx cement,

3rd plug set CIBP at 950',

4th plug perforate at 903' and 873'. Circulate cement to surface with 180 sx.

Remarks: Used 65/35 Pozmix 6% gel by D & S Cementing. No casing recovery.

(If additional description is necessary, use BACK of this form.)

INVOICED
DATE 9-15-93
NV. NO. 38462

Signed Glenn L. Barlow
(TECHNICIAN)

RECEIVED
SEP 09 1993
9-9-93
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
Wichita, Kansas