Operator License # 5056 Operator: F. G. Holl County Name& Address 6427 East Kellogg Well To Gonduct Wichita, KS 67207 Abandoned Oll Well Gas Well Input Well Other well as hereinafter indicated	License Number 5142 onth: August Year: 19 84
Operator: F. G. Holl County Name& Address 6427 East Kellogg Well To Conduct Wichita, KS 67207 Conduct Surface Abandoned Oll Well Gas Well Input Well Other well as hereinafter indicated	Edwards tal Depth
Name& Address 6427 East Kellogg Well To Conduct Conduct Surface Abandoned Oll Well Gas Well Input Well Other well as hereinafter indicated Input Well	tal Depth 4522 1/6. 987 or Pipe: Size feet Casing: Size 8 5/8 feet 248 I SWD Well D&A X License Number 5142
Wichita, KS 67207 Conduct Surface Abandoned Oll Well Gas Well Input Well Other well as hereinafter indicated	Casing: Size 8 5/8 feet 248 SWD Well
Abandoned Oli Weil Gas Well Input Well Other well as hereinafter indicated	Casing: Size 8 5/8 feet 248 SWD Well
Abandoned Oli Weii Gas Weii Input Wei Other well as hereinafter indicated	SWD Well D&A X License Number 5142 onth: August Year:19 84
Other well as hereinafter indicated	License Number 5142 onth: August Year: 19 84
·	License Number 5142 onth: August Year: 19 84
Charles Post 11 to a Ca	onth: August Year:19 84
Plugging Contractor Sterling Drilling Co.	
Address Box 129, Sterling, KS 67579	
Company to plug at: Hour: 7:00 pm Day: 31	Own dor
Plugging proposal received from Vaught Th	ombaon
(company name) Sterling	(phone) 316-278-2131
were: to fill hole with heavy mud and spot ceme	nt through drill pipe
1st plug at 750° with 50 sx cement	
2nd plug at 270' with 40 sx cement solid bridge 3rd plug hulls - plug at 40' cement to surface wi 5th plug to circulate rat hole with 15 sx cement Plug water well with 5 sx cement Plugging Proposal Receiv	th 10 sx cement
Plugging Operations attended by Agent?: All	77
Operations Completed: Hour: 9:45 pm Day: 31	
ACTUAL PLUGGING REPORT 1st plug at 750' with 50 sx c	ement, 2nd plug at 270' with 40 sx
cement, 3rd & 4th plugs - solid bridge - hulls - plu	g at 40' cement to surface with
10 sx cement, 5th plug to circulate rat hole with 15	sx cement, plugged water well
with 5 sx cement	0 5 9/1
Steve Durrant gave these plugging orders.	9-5-84 BEDENIES
	STATE CORPORATION SCHIMISSIUM
Remarks: Used 60/40 Pozmix 2% gel 3% cc by Halliburt (If additional description is necessary)	on # 896325 USO BACK of this forms 05 100 A SONSERVATION DIVISION

INV. NO. 3671

FORM CP-2/3 Rev.01-84