

1 110096

12-15-87

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION S/2 N/2 SE, SEC. 23, T 24 S, R 17 W/EK
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-047-21,307-0000
1650 feet from S section line
1320 feet from E section line

TECHNICIAN'S PLUGGING REPORT
Operator License # 5056

Lease Name Stapleton "B" Well # 1-23
County Edwards 146.90

Operator: F.G. Holl Company
Name & Address P.O. Box 780157
Wichita, KS 67278-0167

Well Total Depth 4520 feet
Conductor Pipe: Size _____ feet
Surface Casing: Size 8 5/8 feet 308

Abandoned Oil Well _____ Gas Well _____ Input Well _____ SWD Well _____ D&A X

Other well as hereinafter indicated _____

Plugging Contractor Sterling Drilling Company License Number 5142

Address Box 129, Sterling, KS 67579

Company to plug at: Hour: 1 p.m. Day: 15 Month: 12 Year: 1987

Plugging proposal received from Von Thompson

(company name) Sterling Drilling Company (phone) 316-278-2131

were: to fill hole with heavy mud and spot cement through drill pipe Anhydrite 1133-46'
Elevation 2100' GL
1st plug at Base Anhydrite with 40 sx cement, 2nd plug at 1/2 Anhydrite with 40 sx cement,
3rd plug at 30' below base of surface pipe with 40 sx cement,
4th plug at 40' with 10 sx cement, 5th plug to circulate rathole with 15 sx cement,
6th plug to circulate mousehole with 10 sx cement.

Plugging Proposal Received by James R. Kapp (TECHNICIAN)

Plugging Operations attended by Agent?: All _____ Part _____ None X

Operations Completed: Hour: 2:15 p.m. Day: 15 Month: 12 Year: 1987

ACTUAL PLUGGING REPORT 1st plug at 1170' with 50 sx cement,
2nd plug at 570' with 40 sx cement,
3rd plug at 340' with 40 sx cement,
4th plug at 40' with 10 sx cement,
5th plug to circulate rathole with 15 sx cement.

Remarks: Used 60/40 Pozmix 6% gel by Halco.
(If additional description is necessary, use BACK of this form.)

INVOICED
did not observe this plugging.

DATE 1-6-88

INV. NO. 19377

Signed James R. Kapp (TECHNICIAN)

12-22-87
STATE CORPORATION COMMISSION
CONSERVATION DIVISION
WICHITA, KANSAS
DEC 22 1987

CORRECTED NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Correction *

Expected Spud Date... December 9, 1987
month day year

API Number 15-047-21,307 - 0000

OPERATOR: License #... 5056
Name... F. G. Holl Company
Address... P. O. Box 780157
City/State/Zip... Wichita, Kansas 67278-0167
Contact Person... Elwyn H. Nagel
Phone... (316) 684-8481

S/2 N/2 SE Sec. 23.. Twp.. 24. S, Rg. 17.... West
..... 1650..... Ft. from South Line of Section
..... 1320..... Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License #... 5142
Name... Sterling Drilling Company
City/State... Sterling, Kansas 67579

Nearest lease or unit boundary line . 990..... feet
County..... Edwards.....

Well Drilled For: Well Class: Type Equipment:
 Oil Storage Infield Mud Rotary
 Gas Inj. Pool Ext. Air Rotary
 OWWO Expl Wildcat Cable

* Lease Name... Stapleton "B" Well #... 1-23
Ground surface elevation ... 2100 est..... feet MSL

Domestic well within 330 feet: yes no
Municipal well within one mile: yes no

If OWWO: old well info as follows:
Operator
Well Name
Comp Date Old Total Depth.....

Depth to bottom of fresh water..... 150.....
Depth to bottom of usable water 280.....

Surface pipe by Alternate: 1 2
Surface pipe planned to be set 300'.....

Conductor pipe required NA.....
Projected Total Depth 4550..... feet

Formation..... Viola.....

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date Dec 8, 1987 Signature of Operator or Agent W. Bryce Bidleman Title..... Geologist

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 300 feet per Alt.

This Authorization Expires 6-4-88 Approved By 12-4-87
12-7-87
12-8-87

#WAS: Stapleton

WW

Spud 12/9/87 1:00

300' 8 1/8" Halliburton

S/2 N/2 SE. Sec. 23... Twp 24... S. Rg. 17... West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).
60/40 Pao w/ 670 28

1st plug @ ft. deep... 1140 or formation with... 40 SX..... feet of..... cement
2nd plug @ ft. deep... 570 1/2 Ank or formation with... 40 SX..... feet of.....
3rd plug @ ft. deep... 300 7/30 or formation with... 40 SX..... feet of.....
4th plug @ ft. deep... 40 or formation with... 10 SX..... feet of cement & 1/2 sx hulls &
5th plug @ ft. deep... or formation with..... feet of Halliburton plug
(2) Rathole to surface minus 5 feet 15 (b) Mousehole to surface minus 5 feet 10

PUSHER <u>Van Thompson</u>	FORMATION <u>Viola</u>	SURFACE PIPE <u>8 1/8" @ 308</u>	ANEHYDRITE <u>1183</u> ELEVATION <u>2100</u>	STARTING TIME & DATE <u>12-13-87 1:00 PM</u>	COMPLETION TIME & DATE <u>12-15-87 2:15 PM</u>	1st PLUG @ <u>1170 FT. W/ 50 SX</u>	2nd PLUG @ <u>570 FT. W/ 40 SX</u>	3rd PLUG @ <u>340 FT. W/ 40 SX</u>	4th PLUG @ <u>40 FT. W/ 10 SX</u>	RAT HOLE CIRCULATED W/ <u>15 SX</u>	MOUSE HOLE CIRCULATED W/ <u>SX</u>	WATER WELL PLUGGED W/ <u>SX</u>	CEMENT COMPANY <u>Haleo</u>	TECHNICIAN <u>60/40 w/ 670</u>
----------------------------	------------------------	----------------------------------	--	--	--	-------------------------------------	------------------------------------	------------------------------------	-----------------------------------	-------------------------------------	------------------------------------	---------------------------------	-----------------------------	--------------------------------

12-22-87

STATE CORPORATION COMMISSION
CONSERVATOR
Wichita, Kansas
UP: 27 1007