STATE CORE	$_1$ 052103	AFI- NUMBER 15- 047-20,248-0000 260' SW of
Wichita State Office Bldg PLUGGING SECTION 130 S. Market, Room 2078 Wichita, KS 67202		C NW , SEC. 14 , T 24 S, R 17 WXX
		3776 feet from S section line
	HIS PLUGGING REPORT	4144 feet from E section line
Operator	License / 5056	Lease Name Miller "B" Well 1 1-14
Operator: Name& Address	F.G. Holl Company, LLC	County Edwards 146.02
	P.O. Box 780167	Well Total Depth 4493 feet
	Wichita, KS 67278-0167	Conductor Pipe: Sizefeet
		Surface Casing: Size 8 5/8 feet 306
Abandonad	1 Oll Well X Gas Well	Imput Well SWD Well D&A
Other we	i as hereinafter indicated	
Plugging	Contractor Pratt Well Service	License Number 5893
Address	P.O. Box 847, Pratt, KS 67124	· · · · · · · · · · · · · · · · · · ·
	to plug at: Hour: 1 p.m. Day:	21 Month: 1 _ Year:19 97 Thom Pool
		·
(company	4½" at 4487 w/125 sx cement, PBTD	(phone) 316-995-3171 4456', Perfs at 4339-4343'
		cement on top of sand through bailer,
		plug pump 50 sx cement at 1194, 4th plug pump 50 sx
at 600'	,	
5th plu	g pump 40 sx cement at 298, 6th	prug ar 40: with 10 sx cement.
	Plugging Pr	oposal Received by Steve Durrant (TECHNICIAN)
'Pluggin	g Operations attended by Agent?:	AllX PartNone
Operati	ons Completed: Hour: 6:40 p.m.Day	: 21 Month: 1 Year:1997
ACTUAL	PLUGGING REPORT lst plug sanded b	ack to 4280 and dumped 4 sx cement on top of sand
	bailer,	
//	g pumped through $4\frac{1}{2}$ " casing at 2	380' with 50 sx cement,
3rd plu	g at 1194' with 50 sx cement,	1-27-97
4th plu	g at 600' with 50 sx cement,	19 A
_	g at 298' with 40 sx cement, 6th	plug at 40' with 10 sx cement.
Remarks	Used 60/40 Pozmix 6% gel by Hal	liburton. Recovered 2442' of:42" casing.
		Is necessary, use BACK of this form.
In Way	AN an coor	Signed Ruchway W. Harry
. 97.12	JAN 2 0 1007:	FORM CP-2/3
'NV. NO		FURM CF-273