(If additional descriptionWirghandessary, use BACK of this form.)

I Nad O lie net Dobserve this plugging.

DATE 12-8-87

env. ng. _

JAN 1 4 1988

(HECHNICIAN)

CARD MUST BE SI

State of Kansas NOTICE OF INTENTION TO DRILL

Expected Spud Date. November 23, 1987 month day year	API Number 15— 155-21,101
5238	CE NE 11 22 9°
OPERATOR: License #	SE NE Sec. 11. Twp. 22. S, Rg. 9
Address 301 N. Main, Suite 900	
City/State/Zip Wichita, KS 67202-1508	(Note: Locate well on Section Plat on reverse side)
Contact Person. Terry Naylor	Nearest lease or unit boundary line
Phone 316 793-8471	CountyReno
CONTRACTOR: License #51.22	County
Name Woodman-Iannitti Drilling Co.	Ground surface elevation
City State 1022 Union Center, Wichita, KS 67202	Domestic well within 330 feet:yes
Well Drilled For: Well Class: Type Equipment:	•
X Oil Storage Infield X Mud Rotary	Municipal well within one mile: Depth to bottom of fresh water
	Depth to bottom of usable water
Gas Inj Pool Ext Air Rotary	
OWWO ExplX Wildcat Cable	Surface pipe by Alternate: 1_
If OWWO: old well info as follows:	Surface pipe by Atternate: 220 *
Operator	Conductor pipe required
Well Name	Projected Total Depth
Comp Date Old Total Depth	FormationAIDUCKIE
I certify that well will comply with K.S.A. 55-101, et seq., plus exentual	Un plugging Hololtoff CC englifications
Date11-13-87 Signature of Operator or Agent	Title District Landman
For KCC Use: Conductor Pipe Required	
	SE NE Sec. 11 Twp
PLUGGING PROPOSA	L IF ABOVE IS D & A
This plugging proposal will be reviewed and approved or revised at the ti 5 p.m. workdays).	me the district office is called prior to setting surface casing (ca
20001	4-14-
Let pluz @ ft. deep 3800'	25 60//ብ
2nd plug @ ft. deep	
2nd plug @ ft. deep	40 feet of 60/40 20 feet of 60/40
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. 60/40 feet of. 60/40 10 Sacks Cement in water well feet and the amount of cement to be used is necessary prior to
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. 60/40 feet of. 60/40 10 Sacks Cement in water well feet and the amount of cement to be used is necessary prior to
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. 60/40 feet of. 60/40 10 Sacks Cement in water well sent and the amount of cement to be used is necessary prior to action casing is cemented in. ip.m. workdays)
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. 60/40 feet of. 60/40 10 Sacks Cement in water well sent and the amount of cement to be used is necessary prior to action casing is cemented in. ip.m. workdays)
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. (b) Mousehole to surface minus 5 feet of water well sent and the amount of cement to be used is necessary prior to action casing is cemented in. 5 p.m. workdays)
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. (b) Mousehole to surface minus 5 feet of. 10 Sacks Cement in water well feet and the amount of cement to be used is necessary prior to action casing is cemented in. is p.m. workdays) sxs at. hours.
2nd plug @ ft. deep	feet of. 60/40 20 feet of. 60/40 feet of. 60/40 feet of. (b) Mousehole to surface minus 5 feet of. 10 Sacks Cement in water well feet and the amount of cement to be used is necessary prior to action casing is cemented in. is p.m. workdays) sxs at. hours.