KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST (See Instructions on Reverse Side)

| Type Test | | | | | | (- | See ins | ииси | ions on He | verse Side | 3) | | | | | | | |
|---|-----------------------|---|---|-------------------------------|---|--|-------------------------|---------------------------|--|---------------------------------------|--|--|-----------------------------|---------------------|--------------------------------|----------------------|--|--|
| | en Flow liverabili | | | | | Test Date |) : | | | | A | API No |), 15 446 | 1044 |)5 – 0(| იიი | | |
| Company | , | | | | | 6/15/15 | , | | Lease HORN | ER A | | | 118 | <i>3</i> -1010 | | | lumber | |
| County MEADE | | Location C NE | | Section 19 | | | TWP 33S | | RNG (E/W) 26W | | | | Acres | Attributed | | | | |
| Field McKINNEY | | | Reservoir CHESTER | | | | | Gas Gathering Co ONEOK | | ring Conn | ection | | | | | | | |
| Completion Date 10/2/1956 | | | | Plug Back Total Depth 5717 | | | h | Packer Set at | | at | | | | | | | | |
| Casing Size | | Weight | | | Internal Diameter | | | Set at 5715 | | Perforations 5684 | | то 5696 | | | | | | |
| Tubing Size 2 3/8 | | | Weigh | Weight | | | Internal Diameter | | | Set at 5684 . | | Perforations | | | То | | | |
| Type Completion (Describe) SINGLE GAS | | | | Type Flui WTR | Type Fluid Production WTR | | | | Pump Unit or Trave | | or Traveling | ing Plunger? Yes / No | | | | | | |
| Producing Thru (Annulus / Tubing) CASING | | | | | % C | arbon [| | | • | % Nitrogen | | | Gas Gravity - G 0.7070 | | | • | | |
| Vertical D | epth(H) | | | | | | ı | Press | sure Taps | | | | | | (Meter | Run) (F | Prover) Size | |
| ²ressure | Buildup | ; S1 | hut in 6/1 | 4 | 20 | 0 15 at 1 | 0:00 a | m | (AM) (PM) | Taken 6/ | 15 | | 20 | 15 at | 10:00 | am | (AM) (PM) | |
| Well on L | ine: | St | tarted | | 20 | 0 at | | | (AM) (PM) | Taken | | | 20 | at | | | , (AM) (PM) | |
| | | | | - | | - | OBSE | RVE | D SURFAC | | | | | Duratio | n of Shut | -in24 | Hours | |
| Static / Orifice Dynamic Size Property (inches) | | | Circle one: Meter Prover Pressure psig (Pm) | | Pressure Differential in Inches H ₂ 0 | Flowing Temperature t | Well He Tempera t | | Casing Wellhead Pressure (P ₂) or (P ₁) or (P _c) psig psia | | (P. | Tubing Wellhead Pressure (P _w) or (P ₁) or (P _c) psig psia | | Duration (Hours) | | Liqu | Liquid Produced (Barrels) Received SAS CORPORATION COA | |
| Shut-In | | | | | | | | | 42 | рыа | ры | 9 | рыа | 24 | | חר | PPORATION CO | |
| Flow | | | | | | | | | | | | | | | | DE | C 28 20 | |
| | | | | | | | FLOW | STR | EAM ATTR | IBUTES | | | | | | W | RVATION DIVIS | |
| Plate Coefficeient (F _b) (F _p) Mcfd | | Circle one: Meter or Prover Pressure psia | | | Eutopolop | | Gravity Factor F | | Flowing emperature Factor F ₁ , | Fa | Deviation Factor F _{pv} | | Metered Flow R (Mcfd) | | GOR (Cubic Feet/ Barrel) | | Flowing Fluid Gravity G _m | |
| | | | | <u> </u> | | (ODEN EL | 0110 /01 | | | | | | | | | | | |
| _ _د)² = | | : | (P _w) ² = | | : | • | | % | E RABILITY 6 (F |) CALCUL P _a - 14.4) + | | | : | | |) ² = 0.1 | 207 | |
| $(P_c)^2 - (P_a)^2$ or $(P_c)^2 - (P_d)^2$ | | (P _c) ² - (P _w) ² | | 1 | se formula 1 or 2: 1. $P_c^2 - P_d^2$ 2. $P_c^2 - P_d^2$ and by: $P_c^2 - P_w^2$ | LOG of formula 1. or 2. and divide by: | | 2 % | Slop | Backpressure Curve Slope ≃ "n" | | x LO | a [] | Ar | ntilog | De | pen Flow liverability s R x Antilog (Mcfd) | |
| | | | | | | | | | | | | | | | | | | |
| Open Flow Mcfd @ | | | | Mcfd @ 14. | | | | Deliverab | | | Mcfe | | | ofd @ 14.65 psia | | | | |
| The | undersig | ned | authority, o | n be | ehalf of the | Company, s | states th | at he | e is duly au | | | | • | ort and t | hat he h | as kno | wledge of | |
| ne facts s | tated th | erein, | , and that sa | aid ı | report is true | and correc | t. Exec | uted | this the _1 | 5th NS | day of | Dec | ember 2 | | | , | , 20 <u>15</u> . | |
| | | | Witness (| if any |) | | · · · · · | | - | 05 | <u>4/17</u> | | For | Company | ` | | | |
| | | | For Comm | oizzin | n | | | _ | - | | | | Che | cked by | | | | |

| | nder penalty of perjury under the laws of the state of K Inder Rule K.A.R. 82-3-304 on behalf of the operator <u>Be</u> | |
|----------------|--|---|
| | regoing pressure information and statements contained | |
| | est of my knowledge and belief based upon available pr | |
| | stallation and/or upon type of completion or upon use be | |
| | quest a one-year exemption from open flow testing for th | |
| | grounds that said well: | |
| ∫ further agr | is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil res is on vacuum at the present time; KCC approval Doc is not capable of producing at a daily rate in excess ree to supply to the best of my ability any and all suppo | cket Nos of 250 mcf/D orting documents deemed by Commission |
| | | Received KANSAS CORPORATION COMMI |
| Date: 12/15/15 | <u>i </u> | DEC 2 8 2015 |
| | | CONSERVATION DIVISION WICHITA, KS |
| | Signature: | Bh |
| | Title: Petroleum Engi | ineer |
| | | |
| | | |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under OBSERVED SURFACE DATA. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption IS denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.