SIDE ONE

information.

	Two (2) copies of this form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within thirty (30) days after the completion of a well, regardless of how the well was completed.										
F	Attach separate letter of request if the information is to be held <u>confidential</u> . If confidential, only file <u>one</u> copy. Information on <u>Side One</u> will be of public record and <u>Side Two</u> will then be held confidential.										
	Applications must be made on dual completion, c iniction and temporarily abandoned wells.	commingling, salt water disposal,									
С	Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238.										
	LICENSE # 5058 EXPIRATION DATE	Е 6-30-83									
	OPERATOR Griggs Oil, Inc.	API NO. 15-185-21,732-0000									
	ADDRESS 1625 KSB&T Bldg.	COUNTY Stafford									
	Wichita, Kansas 67202	FIELD									
	** CONTACT PERSON Virginia L. Smith PHONE 267-1277	PROD. FORMATION N/A									
	PURCHASER N/A	LEASE Scott									
	ADDRESS	WELL NO. 2									
		WELL LOCATION NE SW NW									
		990 Ft. from west Line and									
	CONTRACTOR ADDRESS 3935 Broadway	990 Ft. from south Line of									
	Kansas City, Kansas 64111	the NW (Qtr.) SEC 35 TWP24S RGE 15W.									
	PLUGGING Allied Cementing Co., Inc.	WELL PLAT (Office									
	CONTRACTOR ADDRESS P. O. Box 31	Use Only									
	Russell, Kansas 67665	KCCKGS/_									
	TOTAL DEPTH 4418' PBTD	SWD/REP									
	SPUD DATE 12-31-82 DATE COMPLETED 1-14-83	35 PLG.									
	ELEV: GR 2021' DF 2023' KB 2026'										
	DRILLED WITH KOANNEY (ROTARY) XXXXX TOOLS.										
	DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE										
	Amount of surface pipe set and cemented 386'	DV Tool Used?									
	THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Gas, Injection, Temporarily Abandoned, OWWO. Other	Shut-in Gas, Dry, Disposal,									
	ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATI AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.	ONS PROMULGATED TO REGULATE THE OIL									
,	•										
	A F F T D A U T T										
	<u>AFFIDAVIT</u> Jack S. Griggs	ing of lawful age, hereby certifies									
	that:										
	I am the Affiant, and I am familiar with the co The statements and allegations contained therein are	ntents of the foregoing Affidavit.									
	BOXANA L. MILLER STATE CORPORATION COMMISSION STATE NOTARY PUBLIC Sedgivick County, Karean MAR 1 0 1983	(Name)									
	SUBSCRIBED AND SWORN TO BEFORE ME this 9th	_day of,									
	19 <u>83</u> CONSERVATION DIVISION Wichita, Kansas										
		Parloma & Mills									
	MY COMMITTEE OF THE POST	(NOTARY PUBLIC)									
	MY COMMISSION EXPIRES: April 4, 1984										
	** The person who can be reached by phone regarding	any questions concerning this									

LEASE Scott #2 SEC.35 TWP.24 RGE.15W

FI	LL IN WELL	INFORM	ÁTION AS R	EQUIRED:		WELL NO			- · · · · · · · · · · · · · · · · · · ·	
Show all important s	w all important zones of persity and contents thereof; cored intervaling depth interval tested, cushion used, time tool open, Bowing and s				l <i>drill-</i> ste sures, an	m tosts, in- d racoveries.	SHOW GEOLO OR OTHER D	RKERS, LOGS RUN, /E INFORMATION.		
	N DESCRIPTION,			TOP		воттом	NAMI		DEPTH	
							Sample T Heebner Toronto Douglas Brn Lm Lansing B/KC Conglome Viola Arbuckle RTD	rate	3594 (-1568 3616 (-1590 3632 (-1606 3742 (-1716 3756 (-1730 4012 (-1986 4119 (-2093 4174 (-2148 4412 (-2386 4418 (-2392	
30-45-30-45 Weak blow but Rec. 600' SW IFP 90-204 ISP 1430 FS	-			ighout						
Report of all string	ıs set — surface,	intermedia	ite, production, e	te. CASIN	G RECC	RD (Ne	w) or (Use	d)		
Purpose of string	Sixe hole drilled	Size casing (in O.D.	Weight lbs/ft	. Setting dopt	h T	ypo cement	Sacks		pe and porcent additives	
surface	12-1/4"	8-5/8	24#	389'	607	40 poz	275	3%	cc	
LINER RECORD						PERFORATION RECORD				
op, ft.	Bottom, ft.	200	ks cement	240	ts per ft.	_] _	Size & type	"	epth interval	
	TUBING RECORD Setting depth Packer set at				POPATEON COMMISSION					
ze				V/-						
···—		ACID, FRA	CTURE, SHOT,	CEMENT S	QUEEZE	ORECORD A	3444	 -		
			1 of material used		करम	ina santa mana mana	तनगराका	Pepth inter	val treated	
<u> </u>						<u>. </u>		•		
Sate of first production	· .··	Prod	lucing method (flo	wing, pumping.	, ges lift,	etc.)	Gravi	ts:		
T-1-1-1	Oil									
Estimated Production -I. Disposition of gos (vented	Р.	sold)	bbls.		MCF	Parforat	<u>bbls.</u>	as-oil ratio	CFPB	
,	, vi				}	Perforat	lons			