

To: 1 080433
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 185-22,082-0000
NE NW NE, SEC. 11, T 24 S, R 14 W E
4950 feet from S section line
1650 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5506
Operator: Woolsey Petroleum Corporation
Name & Address: 300 West Douglas, Suite 400
Wichita, KS 67202

Lease Name Billy J. Koelstall # 1
County Stafford
Well Total Depth 4250 138.13 feet
Conductor Pipe: Size feet
Surface Casing: Size 8 5/8" feet 386

Abandoned Oil Well Gas Well Input Well SWD Well D&A

Other well as hereinafter indicated

Plugging Contractor Pratt Well Service License Number 5893
Address P. O. Box 847, Pratt, KS 67124

Company to plug at: Hour: 1:40 pm Day: 23 Month: October Year: 19 85

Plugging proposal received from Ken Gates

(company name) Pratt Well Service (phone) 1-800-362-5097

were: 4 1/2" at 4250' PRTD 4213' Perfs at 3780-4020'

1st plug sand back to 3730' and dump 4 sx cement on top of sand through bailer

2nd plug squeeze well with 3 sx hulls, 15 sx gel, 70 sx cement, 10 sx gel, 1 sack

hulls, release 8 5/8" rubber plug and pump 100 sx cement.

Plugging Proposal Received by Richard W. Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 2:20 pm Day: 23 Month: October Year: 19 85

ACTUAL PLUGGING REPORT 1st plug sanded back to 3730' and dumped 4 sx cement on top of sand through bailer, 2nd plug squeezed well with 3 sx hulls, 15 sx gel, 70 sx cement, 10 sx gel, 1 sack hulls, released 8 5/8" rubber plug and pumped 100 sx cement.

Maximum pressure 500 psi and sht in 250 psi

Remarks: Used 60/40 Pozmix 6% gel by BJ-Titan. Recovered 2100' 4 1/2" casing
(If additional description is necessary, use BACK of this form.)

Jack Luthi observed the plugging
I observed the plugging
RECEIVED
STATE CORPORATION COMMISSION

DATE NOV 4 1985

INV. NO. 10900

NOV 1 1985
CONSERVATION DIVISION
Wichita, Kansas

Signed J. A. [Signature]
(TECHNICIAN)