

STATE OF KANSAS  
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

Give All Information Completely  
Make Required Affidavit  
Mail or Deliver Report to:  
Conservation Division  
State Corporation Commission  
800 Bitting Building  
Wichita, Kansas

NORTH

Section Plat grid with 4 columns and 4 rows.

Locate well correctly on above  
Section Plat

Stafford County, Sec. 2 Twp. 24 Rge. 12 (E) West (W)  
Location as "NE/CNW 1/4 SW 1/4" or footage from lines 990' N. & 990' W. of S/4 Cor.  
Lease Owner Cities Service Oil Company  
Lease Name Porter "B" Well No. 2  
Office Address Bartlesville, Oklahoma  
Character of Well (completed as Oil, Gas or Dry Hole) Oil Well  
Date well completed September 25, 19 50  
Application for plugging filed April 8, 19 53  
Application for plugging approved April 9, 19 53  
Plugging commenced April 17, 19 53  
Plugging completed April 24, 19 53  
Reason for abandonment of well or producing formation Depleted formation.

If a producing well is abandoned, date of last production January 1, 19 53  
Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well M. A. Rives  
Producing formation Douglas Depth to top 3315 Bottom 3791 Total Depth of Well 3829 Feet  
Show depth and thickness of all water, oil and gas formations. P. B. T. D. 3791'

OIL, GAS OR WATER RECORDS

CASING RECORD

Table with 7 columns: Formation, Content, From, To, Size, Put In, Pulled Out. Contains data for 8-5/8" and 5-1/2" casing.

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from \_\_\_\_\_ feet to \_\_\_\_\_ feet for each plug set.

3791-3291' sand  
3291-3251' 5 sacks cement  
3251-1047' mud  
1047- 300' pumped in 15 sacks Howco Jel  
300- base of cellar, wood plug and 90 sacks of cement.

RECEIVED  
STATE CORPORATION COMMISSION  
APR 28 1953  
4-28-53  
CONSERVATION DIVISION  
Wichita, Kansas

(If additional description is necessary, use BACK of this sheet)

Name of Plugging Contractor B. & W. Casing Pulling Company  
Address Great Bend, Kansas

STATE OF Kansas, COUNTY OF Barton, ss.  
V. M. Conover (employee of owner) or (owner or operator) of the above-described well,  
being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) V. M. Conover  
Box 751, Great Bend, Kansas  
(Address)

SUBSCRIBED AND SWORN TO before me this 24th day of April, 19 53

My commission expires March 12, 1955.

Notary Public.

PLUGGING  
FILE SEC 2 T 24 R 124  
BOOK PAGE 91 LINE 20

# WELL RECORD

Company Cities Service Oil Co. Well No. 2 Farm Porter "B"  
 Location 990' North and 990' West of 3/4 Corner Sec. 2 T. 24 R. 12W  
 Elevation 1861 (1859 Gr.) County Stafford State Kansas  
 Drlg. Comm. September 4, 1950 Contractor Holm Drilling Company  
 Drlg. Comp. September 25, 1950 Acid 4000 gals. (see below)  
 T. D. 3829' Initial Prod. Physical Potential: 9 oil, 1 1/2 water, 2 1/2 hrs. (10-27-50)

CASING RECORD:

0-5/8" @ 318' con. 250 sz cement  
 5-1/2" @ 3810' con. 150 sz cement

FORMATION RECORD:

clay	0-50
sand	180
red bed	700
shale & shells	1250
salt	1325
shale & shells	1500
shells & shale	1600
lime	1755
shale & lime	1935
lime & shale	2650
shale & lime	2850
lime & shale	3105
lime	3230
lime & shale	3390
lime	3610
lime & shale	3705
lime	3790
shale & dolomite	3811
3811 RTD = 3811 SIM	
cherty lime	3829 T. D.

Top Lensing	3436'
Top Conglomerate	3739'
Top Kinderhook	3745'
Top Viola	3806'
Penetration	21'
Total Depth	3829'

1 1/2 gals. oil per hr. for 12 hrs. at 3824.

9-19-50 Acidized 1000 gals. at 3824.  
 Pumped 1 bbl. oil per hr.

9-21-50 Acidized 3000 gals. at 3824.  
 9-21-50 Pumped 27 oil, 2 1/2 hrs.

9-25-50 Deepened 3824-29.  
 50 gals. oil and 10 gals. water per hour.

SYFO: 500' 1°  
 1000' 1°  
 1500' 1°  
 2000' 0°  
 2500' 0°  
 3000' 1°  
 3500' 2°

**PLUGGING**  
 FILE SEC 2 T 24 R 12W  
 BOOK PAGE 91 LINE 20

**RECEIVED**  
 STATE CORPORATION COMMISSION  
 APR 9 - 1953  
 CONSERVATION DIVISION  
 Wichita, Kansas