

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION SE NE SE, Sec. 7, T 26 S, R 13 W/E
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15-151-21,377/00-00

1650 feet from N/S section line

330 feet from W/E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5313

Lease Name Frisbie "A" Well # 2

Operator: F & M Oil Co., Inc.
Name & 422 Union Center
Address Wichita, KA 67202

County Pratt

Well Total Depth 4490 feet 145.92

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8 feet 895

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Union Drilling Co., Inc. License Number 5103

Address 422 Union Center, Wichita, KS 67202

Company to plug at: Hour: 5:00 am Day: 24 Month: January Year: 19 84

VERBAL PLUGGING ORDERS GIVEN TO Lyle Casson

(company name) Union Drilling (phone) 316-262-1872

were: to fill hole with heavy mud and spot cement through drill pipe.

1st plug at 930' with 40 sx cement

2nd plug at 460' with 40 sx cement
solid bridge

3rd plug hulls - plug at 40' -- cement to surface with 10 sx cement

5th plug to circulate rathole with 15 sx cement. Plug water well with 5 sx cement.

Signed Richard M. Lacey
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 7:20 am Day: 24 Month: January Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 930' with 40 sc cement, 2nd plug at 460' with 40 sx
cement, 3rd and 4th plugs - solid bridge - hulls - plug at 40' -- cement to surface
with 10 sx cement. 5th plug to circulate rathole with 15 sx cement. Plug water
well with 5 sx cement.

Remarks: Use 60/40 Poz, 2% gel, 3% cc. by Halliburton

I hereby certify that the above plugging instructions were given as herein stated
and that I (~~xxx~~ / did not) observe this plugging.

INVOICED RECEIVED
STATE CORPORATION COMMISSION
DATE 2-1-84 1-26-84
INV. NO. 9295 W JAN 26 1984
CONSERVATION DIVISION
Wichita, Kansas
1-24

Signed Richard M. Lacey
(TECHNICIAN)