

GARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 12 - 10 - 85 month day year

API Number 15- 151-21,750-00-00

OPERATOR: License # 8625 VAC PETROLEUM COMPANY Name 333 N. ROCK RD., #105 Address WICHITA, KANSAS 67206 City/State/Zip L.C. HARMON Contact Person (316) 685-0111 Phone 5829

C-NE-NW-SW Sec. 11 Twp. 29 S, Rg. 15 East 2310 West 4290 Ft. from South Line of Section Ft. from East Line of Section (Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5829 ALDEBARAN DRILLING COMPANY Name WICHITA, KANSAS City/State

Nearest lease or unit boundary line 330 feet County PRATT Lease Name HEWITT Well # 1 Ground surface elevation N/A feet MSL Domestic well within 330 feet: yes X no Municipal well within one mile: yes X no Surface pipe by Alternate: 1 X 2 Depth to bottom of fresh water 170 Depth to bottom of usable water 225 Surface pipe planned to be set 400+ ft Projected Total Depth 4850 feet Formation ARBUCKLE

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications. Date 11-26-85 Signature of Operator or Agent W. Boulton Title Partner

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required feet per All 1 2 This Authorization Expires 5-3-86 Approved By 12-3-85

Spent 12-15-85 Set 437' actual Wayne Boulton

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ ANHYDRITE 50' SX - feet depth with 50' SX - sx of 2nd plug @ 30' 4.50' 40' SX - feet depth with 40' SX - sx of 3rd plug @ 40' SOLID BRIDGE @ 10' SURFACE CEMENT feet depth with 10' SX of 4th plug @ feet depth with sx of 5th plug @ feet depth with sx of (2) Rathole with 10' (b) Mousehole with 10' water well - plug 10' - 1/4" Port - 6" hole.

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. Important: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only: API #15- Legal, T, S, R Surface casing of feet set with sx at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sx on 19 Hole plugged 19, agent STATE CO 1986

JAN 2 1986 1-2-86 CON... MEDICAL...