

155
15-25-00068-0000

STATE OF KANSAS
STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging of formations.

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission,
800 Bittling Building,
Wichita, Kansas

Reno County, Sec. 19 Twp. 23S Rge. (E) 7 (W)

Location as "NE1/4NW1/4SW1/4" or footage from lines SE NW NW

Lease Owner The Atlantic Refining Company

Lease Name Page Well No. 1

Office Address Box 17, Great Bend, Kansas.

Character of Well (Completed as ~~Oil Well~~ Dry Hole) Dry

Date, well completed April 9th, 1937.

Application for plugging filed April 10th, 1937.

Application for plugging approved April 10th, 1937.

Plugging Commenced April 10th, 1937.

Plugging Completed April 11th, 1937.

Reason for abandonment of well or producing formation Dry

If a producing well is abandoned, date of last production 1937.

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes

Name of Conservation Agent who supervised plugging of this well G. T. Alexander

Producing formation Siliceous Lime Depth to top 4069 Bottom 4089 Total Depth of Well 4089 Feet

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
Mississippi Lime	Show Oil & Gas	3680'	3683'	12-1/2"	172' NO	None
				8-5/8"	3678' 00	1290'

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from _____ feet to _____ feet for each plug set.

Filled hole with 11 lb. mud with rotary mud hog and drill pipe. Placed 15 sacks of cement at 180 feet after bridging hole at this depth. Filled surface hole with heavy mud and then placed 15 sacks of cement in last 10 feet of surface hole and 10 sacks around outside of surface pipe.

PLUGGING
FILE 19-23-7W
BOOK PAGE 83 LINE 29

RCW
04-22-39

(If additional description is necessary use BACK of this sheet)

Correspondence regarding this well should be addressed to The Atlantic Refining Company
Address Box 17, Great Bend, Kansas.

STATE OF Kansas, COUNTY OF Barton, SS.

Deway A. Jordan (employee of owner) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Deway A. Jordan

(Address) Box 17, Great Bend, Kansas

SUBSCRIBED AND SWORN to before me this 22nd day of April, 1939

My commission expires Nov 13-1939 Notary Public.

15055-00068-0000

Completed Depth 4089'.

Started 2-10-37
Completed 4-11-37

Contractor - Helmerich & Payne, Inc.

Contract Price - \$4.20 per ft.

Day Work - Rotary, when drill pipe used - 250., when not used - 175.

Standard - 125.

Method of Drilling - ROTARY with CABLE tool completion.

CASING RECORD

Size	Set	Pulled
12 1/2"	172'	none
8-5/8"	3675'	1300'

FORMATION	TOP	BOTTOM	FORMATION	TOP	BOTTOM
Sand and shells	0	172	Lime and shale	3420	3482
Sand rock	172	185	Shale and lime shells	3482	3532
Clay and red rock	185	200	Lime and shale	3532	3555
Clay and sand rock	200	215	Shale streak of lime	3555	3590
Red clay and shells	215	335	Shale and lime shells	3590	3625
Red shale and shells	335	500	Shale	3625	3643
Blue shale and shells	500	855	Chat	3643	3664
Shale shells and salt	855	900	Core	3664	3669
Soft shale	900	1030	Chat	3669	3673
Salt and blue shale	1030	1205	Chert and chat	3673	3681
Salt lime	1205	1280	Bailing hole to 2850' (dated 3-18-37)		
White and gray lime	1280	1310	Drilling cement	3620	3675
Shale	1310	1320	Bottom plug	3675	3678
Lime and shale	1320	1360	Lime	3678	3682
Lime	1360	1405	Brown sand	3682	3685
Lime and shale	1405	1475	Lime	3685	3688
Lime	1475	1505	Sandy lime	3688	3695
Shale and lime	1505	1515	Water sand	3688	3695
Hard white lime	1515	1590	Lime	3695	3735
Blue shale - lime	1590	1630	Shale	3735	3971
Lime	1630	1670	Lime	3971	4000
Shale and lime	1670	1690	Sand and shale	4000	4040
Lime	1690	1715	Hard sand	4040	4055
Shale	1715	1730	Shale	4055	4067
Shale and shells	1730	1790	Shale	4067	4070
Lime	1790	1815	Core - siliceous lime	4070	4078
Redrock	1815	1828	Lime	4078	4089
Lime	1828	1990			
Shale and lime	1990	2030	Plugged bottom of surface pipe with 15 sacks cement. Plugged to top of surface with 15 sacks cement (4-11-37)		
Blue and white shale&lime	2030	2085			
Lime	2085	2140			
Shale streaks, white lime	2140	2175			
Shale	2175	2210			
Shale and shells	2210	2225			
Shale	2225	2232			
Lime	2232	2245			
Shale and lime	2245	2360			
Lime	2360	2400			
Shale and lime shells	2400	2437			
Shale	2437	2462			
Shale and lime	2462	2502			
Sand and lime	2502	2560			
Lime	2560	2672			
Sticky shale	2672	2682			
Lime	2682	2940			
Sandy lime	2940	3053			
Lime and shale	3053	3083			
Shale	3083	3113			
Lime	3113	3420			